



## Safety Data Sheet

# Flexi Film® Corrosion Protection

### SECTION 1. IDENTIFICATION

**Product Identifier** Flexi Film® Corrosion Protection  
**Part number** TNDS8010  
**Product Family** Mixture  
**Recommended Use** Corrosion inhibitor and lubricant.  
**Restrictions on Use** Not applicable.  
**Manufacturer** Shrader Canada Limited, 830 Progress Court, Oakville, ON, L6L 6K1, +1.905.847.0222, www.shradercanada.com  
**Emergency Phone No.** CANUTEC, +1.613.996.6666, Operation hours: 24/7

### SECTION 2. HAZARD IDENTIFICATION

#### Classification

Flammable aerosol - Category 1; Gas under pressure - Compressed gas

#### Label Elements



Danger

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Pressurized container: may burst if heated.

Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Store in a well-ventilated place.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
---------------	---------	---	-------------------	-------------

Product Identifier: Flexi Film® Corrosion Protection - Ver. 1  
Date of Preparation: June 26, 2017  
Date of Last Revision:

SDS No.: TNDS8010

Page 01 of 06

Petroleum gases, liquefied	68476-85-7	10-30		
Lanolin oil	70321-63-0	0.5-1.5		

**Notes**

Concentration ranges due to batch processing. Documentation supporting composition variability is maintained.

**SECTION 4. FIRST-AID MEASURES**

**First-aid Measures**

**Inhalation**

Not a hazard under normal conditions of use.

**Skin Contact**

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs, get medical advice or attention.

**Eye Contact**

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.

**Ingestion**

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Immediately call a Poison Centre or doctor.

**SECTION 5. FIRE-FIGHTING MEASURES**

**Extinguishing Media**

**Suitable Extinguishing Media**

Small fire: carbon dioxide or dry chemical.

**Unsuitable Extinguishing Media**

Do not use a direct stream of water.

**Specific Hazards Arising from the Product**

Flammable aerosol. contents under pressure.  
sprayed product will project a flame on contact with an ignition source.  
containers may explode if heated.

Vapours are heavier than air. May travel a considerable distance to a source of ignition and flash back to a leak or open container. Liquid can float on water and may travel to distant locations and/or spread fire.  
Carbon oxides, and other unidentified organic compounds.

**Special Protective Equipment and Precautions for Fire-fighters**

Use extreme caution, fight fire from a safe distance or a protected location.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment, and Emergency Procedures**

Eliminate all ignition sources. Use grounded, explosion-proof equipment. Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

**Environmental Precautions**

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Do not allow into any sewer, on the ground or into any waterway.

**Methods and Materials for Containment and Cleaning Up**

Stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs. Containers of this material may contain hazardous residues when "emptied". Do not weld, cut or perform hot work on empty container until all traces of product have been removed. It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Wear personal protective equipment to avoid direct contact with this chemical.

### Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated. Empty containers may contain hazardous residue. Store separately. Keep closed. Follow all precautions given on this safety data sheet.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult local authorities for provincial or state exposure limits.

### Appropriate Engineering Controls

Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted. Provide eyewash and safety shower if contact or splash hazard exists.

### Individual Protection Measures

#### Eye/Face Protection

Safety glasses with side shields. Contact lenses should not be worn, they may contribute to the severity of the injury.

#### Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.  
Suitable materials are: neoprene rubber, nitrile rubber.

#### Respiratory Protection

Not normally required if product is used as directed.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

Appearance	Tan Aerosol.
Odour	Hydrocarbon
Odour Threshold	Not available
pH	Not applicable
Melting Point/Freezing Point	Not available (melting)
Initial Boiling Point/Range	Not available
Flash Point	$\geq 150$ °C (closed cup)
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable (liquid).
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	> 1
Relative Density (water = 1)	0.97 at 25 °C (77 °F)
Solubility	Insoluble in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available

Product Identifier: Flexi Film® Corrosion Protection - Ver. 1  
Date of Preparation: June 26, 2017  
Date of Last Revision:

SDS No.: TNDS8010

Page 03 of 06

<b>Decomposition Temperature</b>	Not available
<b>Viscosity</b>	> 14 centistokes at 40°C (kinematic)
<b>Other Information</b>	
<b>Flame projection</b>	> 100 cm, no flashback
<b>NFPA Classification</b>	Aerosol, Level 3

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use.

### Chemical Stability

Stable at ambient temperatures and pressures.

### Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

### Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

### Incompatible Materials

Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric acid).

### Hazardous Decomposition Products

Carbon oxides. And other unidentified organic compounds.

## SECTION 11. TOXICOLOGICAL INFORMATION

Information presented below is for the entire product, unless otherwise specified.

### Likely Routes of Exposure

Inhalation.

Skin contact.

Eye contact.

Ingestion.

### Acute Toxicity

93% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (inhalation).

67% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (oral).

69% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (dermal).

### Skin Corrosion/Irritation

May cause very mild irritation based on information for closely related chemicals.

### Serious Eye Damage/Irritation

May cause very mild irritation based on information for closely related chemicals.

### STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

No hazard under normal conditions of use.

#### Skin Absorption

Not harmful based on information for closely related materials.

#### Ingestion

If small amounts are swallowed not likely to cause injury. If large amounts are swallowed symptoms may include nausea, vomiting, stomach cramps and diarrhea.

### Aspiration Hazard

Not known to be an aspiration hazard.

### Respiratory and/or Skin Sensitization

Product Identifier: Flexi Film® Corrosion Protection - Ver. 1  
 Date of Preparation: June 26, 2017  
 Date of Last Revision:

SDS No.: TNSD8010

Page 04 of 06

Not known to be a respiratory sensitizer.

Not known to be a skin sensitizer.

### Carcinogenicity

Chemical Name	ACGIH®	IARC	NTP	OSHA
Petroleum gases, liquefied	Not Listed	Not Listed	Not Listed	Not Listed

No components are listed as carcinogens by ACGIH, IARC, NTP or OSHA.

### Key to Abbreviations

ACGIH® = American Conference of Governmental Industrial Hygienists. A4 = Not classifiable as a human carcinogen.

IARC = International Agency for Research on Cancer. Group 3 = Not classifiable as to its carcinogenicity to humans.

No information was located for: Development of Offspring, Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

## SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal Methods

The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of in accordance with municipal, provincial/state or federal regulations.

## SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	UN1950	Aerosols	2.1	---
IATA (Air)	UN1950	Aerosols, flammable	2.1	---
IMDG (Marine)	UN1950	Aerosols	2.1	---

**Special Precautions** Not applicable

### Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

**Emergency Response** 126 EmS F-D, S-U

### Guide No.

### Other Information

ICAO/IATA PI Y203/203

Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are met.

## SECTION 15. REGULATORY INFORMATION

### Safety, Health and Environmental Regulations

#### Canada

#### Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

#### USA

#### Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

#### Additional USA Regulatory Lists

CERCLA: Not applicable.

Product Identifier: Flexi Film® Corrosion Protection - Ver. 1

SDS No.: TNSD8010

Date of Preparation: June 26, 2017

Date of Last Revision:

Page 05 of 06

SARA Title III - Section 302: Not applicable.  
SARA Title III - Section 313: Not applicable.  
California Proposition 65: Not applicable.  
Massachusetts Right To Know: Not applicable.  
New Jersey Right To Know. (Petroleum gases, liquefied)

## SECTION 16. OTHER INFORMATION

**NFPA Rating**                      **Health - 0**    **Flammability - 4**                      **Instability - 3**

**SDS Prepared By**                Regulatory Compliance

**Phone No.**                        800.201.9486

**Date of Preparation**            June 26, 2017

**Key to Abbreviations**        ACGIH® = American Conference of Governmental Industrial Hygienists

CANUTEC = Canadian Transportation Emergency Centre

CAS = Chemical Abstract Services

CCOHS = Canadian Centre for Occupational Health & Safety

CNS = Central nervous system

GESTIS Substance Database

HSDB® = Hazardous Substances Data Bank

IARC = International Agency for Research on Cancer

ICAO = International Civil Aviation Organization

IMDG = International Maritime Dangerous Goods Code

LC = Lethal concentration

LD = Lethal dose

NFPA = National Fire Protection Association NTP = National Toxicology Program

OSHA = US Occupational Safety and Health Administration

PPM = Parts per million

RTECS® = Registry of Toxic Effects of Chemical Substances

STEL = Short term exposure limit

TDG = Transportation of Dangerous Goods Regulations (Canada)

TWA = Time weighted average

**References**                        Material Safety Data Sheet from manufacturer.

CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).

HSDB® database. US National Library of Medicine. Available from Canadian Centre for Occupational Health and Safety (CCOHS).

Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault Systèmes/BIOVIA ("BIOVIA"). Available from Canadian Centre for Occupational Health and Safety (CCOHS).

ECHA - European Chemical Agency, Classification and Labelling Inventory

GESTIS Substance Database

OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.

**Disclaimer**

The information contained herein is offered only as a guide to the use and handling of this specific material and has been prepared in good faith. It is not intended to be all-inclusive, and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied. Shrader Canada Limited will not be liable for any damages, losses, injuries or consequential damages which may result from the use of or reliance on any information contained herein.

---

Product Identifier:                Flexi Film® Corrosion Protection - Ver. 1

SDS No.:    TNS8010

Date of Preparation:            June 26, 2017

Date of Last Revision:

Page            06 of 06