

## 1. Identification

|   |   |
|---|---|
| <b>Product identifier</b>                                     | <b>2 Cycle +</b>  |
| <b>Other means of identification</b>                          | Not available.  |
| <b>Recommended use</b>  | Lubricant / Oil   |
| <b>Recommended restrictions</b>                               | None known.   |
| <b>Manufacturer/Importer/Supplier/Distributor information</b> |   |
| <b>Manufacturer</b>   |   |
| <b>Company name</b>   | Irving Blending & Packaging   |
| <b>Address</b>  | 555 Courtenay Bay Causeway<br>Saint John<br>NB<br>E2L 4E6<br>Canada |
| <b>Telephone</b>  | 1.800.574.5823  |
| <b>E-mail</b>   | Not available.  |
| <b>Emergency phone number</b>                                 | 1.800.424.9300 (CHEMTREC)   |
| <b>Supplier</b>   | See above.  |

## 2. Hazard identification

|                                   |   |            |
|-----------------------------------|---|------------|
| <b>Physical hazards</b>           | Flammable liquids                                 | Category 3 |
| <b>Health hazards</b>             | Skin corrosion/irritation                         | Category 2 |
|                                   | Serious eye damage/eye irritation                 | Category 2 |
|                                   | Carcinogenicity                                   | Category 2 |
|                                   | Specific target organ toxicity, repeated exposure | Category 1 |
| <b>Environmental hazards</b>      | Not classified.                                   |            |
| <b>WHMIS 2015 defined hazards</b> | Not classified                                    |            |
| <b>Label elements</b>             |   |            |



|  |   |
|--|---|
| <b>Signal word</b>   | Danger  |
| <b>Hazard statement</b>  | Flammable liquid and vapor. Causes skin irritation. Causes eye irritation. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.   |
| <b>Precautionary statement</b>                                       |   |
| <b>Prevention</b>  | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves, protective clothing, eye protection and face protection. Wash thoroughly after handling. Do not breathe the mist or vapor. Do not eat, drink or smoke when using this product. |
| <b>Response</b>  | In case of fire: Use appropriate media to extinguish. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Specific treatment (see information on this label). If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF exposed or concerned: Get medical attention. Get medical attention if you feel unwell.  |
| <b>Storage</b>   | Store in a well-ventilated place. Keep cool. Store locked up.   |
| <b>Disposal</b>  | Dispose of container in accordance with local, regional, national and international regulations.  |
| <b>WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)</b> | None known  |

|  |                 |
|--|-----------------|
| <b>WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)</b> | None known      |
| <b>Hazard(s) not otherwise classified (HNOC)</b>                       | None known.     |
| <b>Supplemental information</b>  | Not applicable. |

### 3. Composition/Information on ingredients

#### Mixture

| Chemical name   | Common name and synonyms | CAS number | %      |
|---|--------------------------|------------|--------|
| Benzene, 1,2,4-trimethyl-                               |                          | 95-63-6    | 1-5*   |
| Butene, homopolymer                                     |                          | 9003-29-6  | 5-10*  |
| Distillates (petroleum), solvent-dewaxed heavy paraffin |                          | 64742-65-0 | 3-7*   |
| Ethylbenzene  |                          | 100-41-4   | 0.1-1* |
| Naphthalene   |                          | 91-20-3    | 0.1-1* |
| Nonane  |                          | 111-84-2   | 1-5*   |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy      |                          | 64742-70-7 | 30-60* |
| Stoddard solvent  |                          | 8052-41-3  | 15-40* |
| White mineral oil (petroleum)                           |                          | 8042-47-5  | 1-5*   |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

|                             |  |
|-----------------------------|--|
| <b>Composition comments</b> | *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.<br>US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. |
|-----------------------------|--|

### 4. First-aid measures

|   |   |
|---|---|
| <b>Inhalation</b>   | If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.  |
| <b>Skin contact</b>   | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Specific treatment (see information on this label). If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. |
| <b>Eye contact</b>  | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.   |
| <b>Ingestion</b>  | Rinse mouth. DO NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.                                 |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Exposed individuals may experience eye tearing, redness and discomfort. Skin irritation. May cause redness and pain.  |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Symptoms may be delayed.   |
| <b>General information</b>  | Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.   |

### 5. Fire-fighting measures

|  |   |
|--|---|
| <b>Suitable extinguishing media</b>                                  | Water fog. Foam. Dry chemical powder. Carbon dioxide.   |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.                        |
| <b>Specific hazards arising from the chemical</b>                    | During fire, gases hazardous to health may be formed.   |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| <b>Fire-fighting equipment/instructions</b>                          | Move containers from fire area if you can do so without risk.                                 |
| <b>Specific methods</b>  | Use standard firefighting procedures and consider the hazards of other involved materials.    |
| <b>General fire hazards</b>  | Flammable liquid and vapor.   |
| <b>Hazardous combustion products</b>                                 | May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.   |

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use care in handling/storage. Avoid contact with eyes, skin and clothing.

### Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/Personal protection

### Occupational exposure limits

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components   | Type | Value      | Form  |
|--|------|------------|-------|
| Benzene, 1,2,4-trimethyl-<br>(CAS 95-63-6)                                     | TWA  | 123 mg/m3  |       |
|  |      | 25 ppm     |       |
| Distillates (petroleum),<br>solvent-dewaxed heavy<br>paraffin (CAS 64742-65-0) | STEL | 10 mg/m3   | Mist. |
|  | TWA  | 5 mg/m3    | Mist. |
| Ethylbenzene (CAS<br>100-41-4)   | STEL | 543 mg/m3  |       |
|  |      | 125 ppm    |       |
| Naphthalene (CAS 91-20-3)  | TWA  | 434 mg/m3  |       |
|  |      | 100 ppm    |       |
| Nonane (CAS 111-84-2)  | STEL | 79 mg/m3   |       |
|  |      | 15 ppm     |       |
| Paraffin Oils (petroleum),<br>Catalytic Dewaxed Heavy<br>(CAS 64742-70-7)      | TWA  | 52 mg/m3   |       |
|  |      | 10 ppm     |       |
| Stoddard solvent (CAS<br>8052-41-3)  | TWA  | 1050 mg/m3 |       |
|  |      | 200 ppm    |       |
| White mineral oil<br>(petroleum) (CAS<br>8042-47-5)                            | STEL | 10 mg/m3   | Mist. |
|  | TWA  | 5 mg/m3    | Mist. |

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

| <b>Components</b>  | <b>Type</b> | <b>Value</b> | <b>Form</b> |
|--|-------------|--------------|-------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                                  | TWA         | 25 ppm       |             |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | TWA         | 1 mg/m3      | Mist.       |
| Ethylbenzene (CAS 100-41-4)  | TWA         | 20 ppm       |             |
| Naphthalene (CAS 91-20-3)  | TWA         | 10 ppm       |             |
| Nonane (CAS 111-84-2)  | TWA         | 200 ppm      |             |
| Stoddard solvent (CAS 8052-41-3)   | STEL        | 580 mg/m3    |             |
|  | TWA         | 290 mg/m3    |             |
| White mineral oil (petroleum) (CAS 8042-47-5)                            | TWA         | 1 mg/m3      | Mist.       |

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

| <b>Components</b>  | <b>Type</b> | <b>Value</b> | <b>Form</b>         |
|--|-------------|--------------|---------------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                                  | TWA         | 25 ppm       |                     |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | TWA         | 5 mg/m3      | Inhalable fraction. |
| Ethylbenzene (CAS 100-41-4)  | TWA         | 20 ppm       |                     |
| Naphthalene (CAS 91-20-3)  | TWA         | 10 ppm       |                     |
| Nonane (CAS 111-84-2)  | TWA         | 200 ppm      |                     |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)      | TWA         | 5 mg/m3      | Inhalable fraction. |
| Stoddard solvent (CAS 8052-41-3)   | TWA         | 100 ppm      |                     |
| White mineral oil (petroleum) (CAS 8042-47-5)                            | TWA         | 5 mg/m3      | Inhalable fraction. |

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

| <b>Components</b>   | <b>Type</b> | <b>Value</b> | <b>Form</b>         |
|---|-------------|--------------|---------------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                             | TWA         | 25 ppm       |                     |
| Ethylbenzene (CAS 100-41-4)   | TWA         | 20 ppm       |                     |
| Naphthalene (CAS 91-20-3)   | TWA         | 10 ppm       |                     |
| Nonane (CAS 111-84-2)   | TWA         | 200 ppm      |                     |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) | TWA         | 5 mg/m3      | Inhalable fraction. |
| Stoddard solvent (CAS 8052-41-3)                                    | TWA         | 100 ppm      |                     |
| White mineral oil (petroleum) (CAS 8042-47-5)                       | TWA         | 5 mg/m3      | Inhalable fraction. |

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

| <b>Components</b>  | <b>Type</b> | <b>Value</b> | <b>Form</b> |
|--|-------------|--------------|-------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                                  | TWA         | 123 mg/m3    |             |
|  |             | 25 ppm       |             |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | STEL        | 10 mg/m3     | Mist.       |

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

| <b>Components</b>   | <b>Type</b> | <b>Value</b> | <b>Form</b> |
|---|-------------|--------------|-------------|
|   | TWA         | 5 mg/m3      | Mist.       |
| Ethylbenzene (CAS 100-41-4)   | STEL        | 543 mg/m3    |             |
|   |             | 125 ppm      |             |
|   | TWA         | 434 mg/m3    |             |
|   |             | 100 ppm      |             |
| Naphthalene (CAS 91-20-3)   | STEL        | 79 mg/m3     |             |
|   |             | 15 ppm       |             |
|   | TWA         | 52 mg/m3     |             |
|   |             | 10 ppm       |             |
| Nonane (CAS 111-84-2)   | TWA         | 1050 mg/m3   |             |
|   |             | 200 ppm      |             |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) | STEL        | 10 mg/m3     | Mist.       |
|   | TWA         | 5 mg/m3      | Mist.       |
| Stoddard solvent (CAS 8052-41-3)                                    | TWA         | 525 mg/m3    |             |
|   |             | 100 ppm      |             |
| White mineral oil (petroleum) (CAS 8042-47-5)                       | STEL        | 10 mg/m3     | Mist.       |
|   | TWA         | 5 mg/m3      | Mist.       |

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)**

| <b>Components</b>  | <b>Type</b> | <b>Value</b> |
|--|-------------|--------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                                  | 15 minute   | 30 ppm       |
|  | 8 hour      | 25 ppm       |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | 15 minute   | 10 mg/m3     |
|  | 8 hour      | 5 mg/m3      |
| Ethylbenzene (CAS 100-41-4)  | 15 minute   | 125 ppm      |
|  | 8 hour      | 100 ppm      |
| Naphthalene (CAS 91-20-3)  | 15 minute   | 15 ppm       |
|  | 8 hour      | 10 ppm       |
| Nonane (CAS 111-84-2)  | 15 minute   | 250 ppm      |
|  | 8 hour      | 200 ppm      |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)      | 15 minute   | 10 mg/m3     |
|  | 8 hour      | 5 mg/m3      |
| Stoddard solvent (CAS 8052-41-3)   | 15 minute   | 125 ppm      |
|  | 8 hour      | 100 ppm      |
| White mineral oil (petroleum) (CAS 8042-47-5)                            | 15 minute   | 10 mg/m3     |
|  | 8 hour      | 5 mg/m3      |

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| <b>Components</b>  | <b>Type</b> | <b>Value</b> | <b>Form</b> |
|--|-------------|--------------|-------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | PEL         | 5 mg/m3      | Mist.       |
|  |             | 2000 mg/m3   |             |
|  |             | 500 ppm      |             |

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| <b>Components</b>   | <b>Type</b> | <b>Value</b>          | <b>Form</b> |
|---|-------------|-----------------------|-------------|
| Ethylbenzene (CAS 100-41-4)   | PEL         | 435 mg/m3<br>100 ppm  |             |
| Naphthalene (CAS 91-20-3)   | PEL         | 50 mg/m3<br>10 ppm    |             |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) | PEL         | 5 mg/m3               | Mist.       |
| Stoddard solvent (CAS 8052-41-3)                                    | PEL         | 2900 mg/m3<br>500 ppm |             |
| White mineral oil (petroleum) (CAS 8042-47-5)                       | PEL         | 5 mg/m3               | Mist.       |

**US. ACGIH Threshold Limit Values**

| <b>Components</b>  | <b>Type</b> | <b>Value</b> | <b>Form</b>         |
|--|-------------|--------------|---------------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                                  | TWA         | 25 ppm       |                     |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | TWA         | 5 mg/m3      | Inhalable fraction. |
| Ethylbenzene (CAS 100-41-4)  | TWA         | 20 ppm       |                     |
| Naphthalene (CAS 91-20-3)  | TWA         | 10 ppm       |                     |
| Nonane (CAS 111-84-2)  | TWA         | 200 ppm      |                     |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)      | TWA         | 5 mg/m3      | Inhalable fraction. |
| Stoddard solvent (CAS 8052-41-3)   | TWA         | 100 ppm      |                     |
| White mineral oil (petroleum) (CAS 8042-47-5)                            | TWA         | 5 mg/m3      | Inhalable fraction. |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| <b>Components</b>  | <b>Type</b> | <b>Value</b>          | <b>Form</b> |
|--|-------------|-----------------------|-------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                                  | TWA         | 125 mg/m3<br>25 ppm   |             |
|  | Ceiling     | 1800 mg/m3            |             |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | STEL        | 10 mg/m3              | Mist.       |
|  | TWA         | 5 mg/m3               | Mist.       |
|  |             |                       |             |
| Ethylbenzene (CAS 100-41-4)  | STEL        | 545 mg/m3<br>125 ppm  |             |
|  | TWA         | 435 mg/m3<br>100 ppm  |             |
| Naphthalene (CAS 91-20-3)  | STEL        | 75 mg/m3<br>15 ppm    |             |
|  | TWA         | 50 mg/m3<br>10 ppm    |             |
| Nonane (CAS 111-84-2)  | TWA         | 1050 mg/m3<br>200 ppm |             |
|  |             |                       |             |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)      | STEL        | 10 mg/m3              | Mist.       |
|  | TWA         | 5 mg/m3               | Mist.       |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                                    | Type    | Value      | Form  |
|---|---------|------------|-------|
| Stoddard solvent (CAS 8052-41-3)              | Ceiling | 1800 mg/m3 |       |
|   | TWA     | 350 mg/m3  |       |
| White mineral oil (petroleum) (CAS 8042-47-5) | STEL    | 10 mg/m3   | Mist. |
|   | TWA     | 5 mg/m3    | Mist. |

**Biological limit values****ACGIH Biological Exposure Indices**

| Components                  | Value    | Determinant                                   | Specimen            | Sampling Time |
|-----------------------------|----------|---|---------------------|---------------|
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines****Canada - Alberta OELs: Skin designation**

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

Naphthalene (CAS 91-20-3) Danger of cutaneous absorption

**Canada - Ontario OELs: Skin designation**

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

Naphthalene (CAS 91-20-3) Danger of cutaneous absorption

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Impervious gloves. Confirm with reputable supplier first.

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection**

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards**

Not applicable.

**General hygiene considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

## 9. Physical and chemical properties

---

|  |                   |
|--|-------------------|
| <b>Appearance</b>                              | Liquid            |
| <b>Physical state</b>                          | Liquid.           |
| <b>Form</b>                                    | Liquid            |
| <b>Color</b>                                   | Dark blue / Green |
| <b>Odor</b>                                    | Petroleum         |
| <b>Odor threshold</b>                          | Not available.    |
| <b>pH</b>                                      | Not available.    |
| <b>Melting point/freezing point</b>            | Not available.    |
| <b>Initial boiling point and boiling range</b> | Not available.    |

|   |  |
|---|--|
| <b>Pour point</b>                                   | -54.4 °F (-48 °C)                            |
| <b>Specific gravity</b>                             | Not available.                               |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.                               |
| <b>Flash point</b>                                  | 130.1 °F (54.5 °C) Pensky-Martens Closed Cup |
| <b>Evaporation rate</b>                             | Not available.                               |
| <b>Flammability (solid, gas)</b>                    | Not applicable.                              |
| <b>Upper/lower flammability or explosive limits</b> |  |
| <b>Flammability limit - lower (%)</b>               | Not available.                               |
| <b>Flammability limit - upper (%)</b>               | Not available.                               |
| <b>Explosive limit - lower (%)</b>                  | Not available.                               |
| <b>Explosive limit - upper (%)</b>                  | Not available.                               |
| <b>Vapor pressure</b>                               | Not available.                               |
| <b>Vapor density</b>                                | Not available.                               |
| <b>Relative density</b>                             | 0.8651 @ 15°C                                |
| <b>Solubility(ies)</b>                              | Insoluble                                    |
| <b>Auto-ignition temperature</b>                    | Not available.                               |
| <b>Decomposition temperature</b>                    | Not available.                               |
| <b>Viscosity</b>                                    | 6.2 cSt @ 100°C<br>27.6 cSt @ 40°C           |

---

## 10. Stability and reactivity

---

|   |   |
|---|---|
| <b>Reactivity</b>                         | This product may react with strong oxidizing agents.  |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.                                 |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Conditions to avoid</b>                | Avoid temperatures exceeding the flash point. Contact with incompatible materials.          |
| <b>Incompatible materials</b>             | Strong oxidizing agents.  |
| <b>Hazardous decomposition products</b>   | May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. |

---

## 11. Toxicological information

---

|   |  |
|---|--|
| <b>Routes of exposure</b>   | Inhalation. Ingestion. Skin contact. Eye contact.  |
| <b>Information on likely routes of exposure</b>                                     |  |
| <b>Ingestion</b>  | May cause stomach distress, nausea or vomiting.  |
| <b>Inhalation</b>   | Prolonged inhalation may be harmful.   |
| <b>Skin contact</b>   | Causes skin irritation.  |
| <b>Eye contact</b>  | Causes eye irritation.   |
| <b>Symptoms related to the physical, chemical and toxicological characteristics</b> | Exposed individuals may experience eye tearing, redness and discomfort. Skin irritation. May cause redness and pain. |

### Information on toxicological effects

#### Acute toxicity

| Components                              | Species | Test Results               |
|---|---------|----------------------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6) |         |                            |
| <b>Acute</b>                            |         |                            |
| <i>Dermal</i>                           |         |                            |
| LD50                                    | Rat     | 3440 mg/kg, 24 Hours, ECHA |
| <i>Inhalation</i>                       |         |                            |
| LC50                                    | Rat     | 10200 mg/m3, 4 Hours, ECHA |
| <i>Oral</i>                             |         |                            |
| LD50                                    | Rat     | 6000 mg/kg, ECHA           |



| Components   | Species | Test Results   |
|--|---------|--|
| Butene, homopolymer (CAS 9003-29-6)                                      |         |  |
| <b>Acute</b>   |         |  |
| <i>Dermal</i>  |         |  |
| LD50   | Rat     | > 2020 mg/kg, Hours, ECHA                                    |
| <i>Inhalation</i>  |         |  |
| LC50   | Rat     | > 6360 mg/m3, ECHA   |
| <i>Oral</i>  |         |  |
| LD50   | Rat     | > 5050 mg/kg, ECHA   |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) |         |  |
| <b>Acute</b>   |         |  |
| <i>Dermal</i>  |         |  |
| LD50   | Rabbit  | > 5000 mg/kg, 24 Hours, ECHA<br>> 2000 mg/kg, 24 Hours, ECHA |
| <i>Inhalation</i>  |         |  |
| LC50   | Rat     | 2.2 mg/L, 4 Hours, ECHA                                      |
| <i>Oral</i>  |         |  |
| LD50   | Rat     | > 5000 mg/kg, ECHA   |
| Ethylbenzene (CAS 100-41-4)  |         |  |
| <b>Acute</b>   |         |  |
| <i>Dermal</i>  |         |  |
| LD50   | Rabbit  | 17.8 ml/kg, 24 Hours, ECHA                                   |
| <i>Inhalation</i>  |         |  |
| LC50   | Rat     | 17629 mg/m3, 4 Hours, ECHA                                   |
| <i>Oral</i>  |         |  |
| LD50   | Rat     | 3500 mg/kg, ECHA   |
| Naphthalene (CAS 91-20-3)  |         |  |
| <b>Acute</b>   |         |  |
| <i>Dermal</i>  |         |  |
| LD50   | Rat     | > 2500 mg/kg, ECHA   |
| <i>Inhalation</i>  |         |  |
| LC50   | Rat     | > 78 ppm, 4 Hours, ECHA<br>> 0.4 mg/L, 4 Hours, ECHA         |
| <i>Oral</i>  |         |  |
| LD50   | Mouse   | 710 mg/kg, ECHA  |
| Nonane (CAS 111-84-2)  |         |  |
| <b>Acute</b>   |         |  |
| <i>Dermal</i>  |         |  |
| LD50   | Rabbit  | > 2000 mg/kg, 24 Hours, ECHA                                 |
| <i>Inhalation</i>  |         |  |
| LC50   | Rat     | 17 mg/L, 4 Hours, ECHA                                       |
| <i>Oral</i>  |         |  |
| LD50   | Rat     | > 5000 mg/kg, ECHA   |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)      |         |  |
| <b>Acute</b>   |         |  |
| <i>Dermal</i>  |         |  |
| LD50   | Rabbit  | > 5000 mg/kg, 24 Hours, ECHA                                 |
| <i>Inhalation</i>  |         |  |
| LC50   | Rat     | > 5.5 mg/L, 4 Hours, ECHA                                    |
| <i>Oral</i>  |         |  |
| LD50   | Rat     | > 5000 mg/kg, ECHA   |
| Stoddard solvent (CAS 8052-41-3)   |         |  |
| <b>Acute</b>   |         |  |
| <i>Dermal</i>  |         |  |
| LD50   | Rabbit  | > 3000 mg/kg, ECHA   |

| Components   | Species  | Test Results  |
|--|--|---|
| <i>Inhalation</i><br>LC50  | Rat  | > 5500 mg/m <sup>3</sup><br>> 5.5 mg/l/4h, ECHA                               |
| <i>Oral</i><br>LD50  | Rat  | > 5000 mg/kg, ECHA  |
| White mineral oil (petroleum) (CAS 8042-47-5)                              |  |   |
| <b>Acute</b>   |  |   |
| <i>Dermal</i><br>LD50  | Rabbit   | > 2000 mg/kg, 24 Hours, ECHA  |
| <i>Inhalation</i><br>LC50  | Rat  | > 5 mg/L, 4 Hours, ECHA   |
| <i>Oral</i><br>LD50  | Rat  | > 5000 mg/kg, ECHA  |
| <b>Skin corrosion/irritation</b>   | Causes skin irritation.  |   |
| <b>Exposure minutes</b>  | Not available.   |   |
| <b>Erythema value</b>  | Not available.   |   |
| <b>Oedema value</b>  | Not available.   |   |
| <b>Serious eye damage/eye irritation</b>                                   | Causes eye irritation.   |   |
| <b>Corneal opacity value</b>   | Not available.   |   |
| <b>Iris lesion value</b>   | Not available.   |   |
| <b>Conjunctival reddening value</b>  | Not available.   |   |
| <b>Conjunctival oedema value</b>   | Not available.   |   |
| <b>Recover days</b>  | Not available.   |   |
| <b>Respiratory or skin sensitization</b>                                   |  |   |
| <b>Respiratory sensitization</b>   | Not available.   |   |
| <b>Skin sensitization</b>  | This product is not expected to cause skin sensitization.  |   |
| <b>Mutagenicity</b>  | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |   |
| <b>Carcinogenicity</b>   | Suspected of causing cancer.   |   |
| <b>ACGIH Carcinogens</b>   |  |   |
| Ethylbenzene (CAS 100-41-4)  |  | A3 Confirmed animal carcinogen with unknown relevance to humans.              |
| Naphthalene (CAS 91-20-3)  |  | A3 Confirmed animal carcinogen with unknown relevance to humans.              |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)        |  | A2 Suspected human carcinogen.  |
| <b>California Proposition 65 - CRT: Listed date/Carcinogenic substance</b> |  |   |
| Cumene (CAS 98-82-8)   |  |   |
| Ethylbenzene (CAS 100-41-4)  |  |   |
| Naphthalene (CAS 91-20-3)  |  |   |
| <b>Canada - Manitoba OELs: carcinogenicity</b>                             |  |   |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)   |  | Suspected human carcinogen.   |
| Ethylbenzene (CAS 100-41-4)  |  | Confirmed animal carcinogen with unknown relevance to humans.                 |
| Naphthalene (CAS 91-20-3)  |  | Confirmed animal carcinogen with unknown relevance to humans.                 |
| Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)        |  | Suspected human carcinogen.   |
| <b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>              |  |   |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)   |  | Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans. |
| Ethylbenzene (CAS 100-41-4)  |  | Volume 77 - 2B Possibly carcinogenic to humans.                               |
| Naphthalene (CAS 91-20-3)  |  | Volume 82 - 2B Possibly carcinogenic to humans.                               |
| Stoddard solvent (CAS 8052-41-3)   |  | Volume 47 - 3 Not classifiable as to carcinogenicity to humans.               |
| White mineral oil (petroleum) (CAS 8042-47-5)                              |  | Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans. |
| <b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)</b>      |  |   |
| Not listed.  |  |   |

**US NTP Report on Carcinogens: Anticipated carcinogen**

Naphthalene (CAS 91-20-3)

Reasonably Anticipated to be a Human Carcinogen.

**US NTP Report on Carcinogens: Known carcinogen**

Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)

Known To Be Human Carcinogen.

Naphthalene (CAS 91-20-3)

Known To Be Human Carcinogen.

Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)

Known To Be Human Carcinogen.

|   |  |
|---|--|
| <b>Reproductive toxicity</b>                              | This product is not expected to cause reproductive or developmental effects.       |
| <b>Teratogenicity</b>                                     | Not available.   |
| <b>Specific target organ toxicity - single exposure</b>   | Not classified.  |
| <b>Specific target organ toxicity - repeated exposure</b> | Causes damage to organs through prolonged or repeated exposure.                    |
| <b>Aspiration hazard</b>                                  | Not an aspiration hazard.  |
| <b>Chronic effects</b>                                    | Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. |

**12. Ecological information****Ecotoxicity** See below**Ecotoxicological data**

| Components   |      | Species                                       | Test Results               |
|--|------|---|----------------------------|
| Benzene, 1,2,4-trimethyl- (CAS 95-63-6)                                  |      |   |                            |
| Crustacea  | EC50 | Daphnia                                       | 6.14 mg/L, 48 Hours        |
| <b>Aquatic</b>   |      |   |                            |
| Fish   | LC50 | Fathead minnow ( <i>Pimephales promelas</i> ) | 7.19 - 8.28 mg/L, 96 hours |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) |      |   |                            |
| Crustacea  | EC50 | Daphnia                                       | 1000 mg/L, 48 Hours        |
| Ethylbenzene (CAS 100-41-4)  |      |   |                            |
| Algae  | IC50 | Algae   | 4.6 mg/L, 72 Hours         |
| Crustacea  | EC50 | Daphnia                                       | 2.1 mg/L, 48 Hours         |
| <b>Aquatic</b>   |      |   |                            |
| Crustacea  | EC50 | Water flea ( <i>Daphnia magna</i> )           | 1.37 - 4.4 mg/L, 48 hours  |
| Fish   | LC50 | Fathead minnow ( <i>Pimephales promelas</i> ) | 7.5 - 11 mg/L, 96 hours    |
| Naphthalene (CAS 91-20-3)  |      |   |                            |
| Algae  | IC50 | Algae   | 0.4 mg/L, 72 Hours         |
| Crustacea  | EC50 | Daphnia                                       | 2.16 mg/L, 48 Hours        |
| <b>Aquatic</b>   |      |   |                            |
| Crustacea  | EC50 | Water flea ( <i>Daphnia magna</i> )           | 1.09 - 3.4 mg/L, 48 hours  |
| Fish   | LC50 | Pink salmon ( <i>Oncorhynchus gorbuscha</i> ) | 1.11 - 1.68 mg/L, 96 hours |

|                                      |   |
|--------------------------------------|---|
| <b>Persistence and degradability</b> | No data is available on the degradability of this product.  |
| <b>Bioaccumulative potential</b>     | No data available.  |
| <b>Mobility in soil</b>              | No data available.  |
| <b>Mobility in general</b>           | Not available.  |
| <b>Other adverse effects</b>         | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

**13. Disposal considerations**

|  |  |
|--|--|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.                         |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.   |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.   |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| <b>Contaminated packaging</b>                | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.       |

## 14. Transport information

**Transport of Dangerous Goods (TDG) Proof of Classification** Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

### U.S. Department of Transportation (DOT)

#### Basic shipping requirements:

UN number UN1268  
Proper shipping name Petroleum distillates, n.o.s.  
Hazard class 3  
Packing group III  
Special provisions 144, B1, IB3, T4, TP1, TP29  
Packaging exceptions 150  
Packaging non bulk 203  
Packaging bulk 242

### Transportation of Dangerous Goods (TDG - Canada)

#### Basic shipping requirements:

UN number UN1268  
Proper shipping name PETROLEUM DISTILLATES, N.O.S.  
Hazard class 3  
Packing group III  
Special provisions 91, 92, 150

### DOT



### TDG



## 15. Regulatory information

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

#### Canada CEPA Schedule I: Listed substance

Naphthalene (CAS 91-20-3) Listed.

#### Canada DSL Challenge Substances: Listed substance

Naphthalene (CAS 91-20-3) Listed.

#### Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Benzene, 1,2,4-trimethyl- (CAS 95-63-6) 1 TONNES

Nonane (CAS 111-84-2) 1 TONNES

Stoddard solvent (CAS 8052-41-3) 1 TONNES

White mineral oil (petroleum) (CAS 8042-47-5) 1 TONNES

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Precursor Control Regulations

Not regulated.

**WHMIS 2015 Exemptions** Not applicable

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Nonane (CAS 111-84-2) 1.0 % One-Time Export Notification only.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Ethylbenzene (CAS 100-41-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Nonane (CAS 111-84-2) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313 (TRI reporting)**

| Chemical name             | CAS number | % by wt. |
|---------------------------|------------|----------|
| Benzene, 1,2,4-trimethyl- | 95-63-6    | 1-5*     |
| Ethylbenzene              | 100-41-4   | 0.1-1*   |
| Naphthalene               | 91-20-3    | 0.1-1*   |

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)  
Naphthalene (CAS 91-20-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**US state regulations**

See below

**US - California Hazardous Substances (Director's): Listed substance**

Benzene, 1,2,4-trimethyl- (CAS 95-63-6) Listed.  
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.  
Ethylbenzene (CAS 100-41-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Nonane (CAS 111-84-2) Listed.  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed.  
White mineral oil (petroleum) (CAS 8042-47-5) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Ethylbenzene (CAS 100-41-4)  
Naphthalene (CAS 91-20-3)  
Nonane (CAS 111-84-2)

**US - Louisiana Spill Reporting: Listed substance**

Ethylbenzene (CAS 100-41-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Nonane (CAS 111-84-2) Listed.

**US - Minnesota Haz Subs: Listed substance**

Benzene, 1,2,4-trimethyl- (CAS 95-63-6) Listed.  
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.  
Ethylbenzene (CAS 100-41-4) Listed.  
Naphthalene (CAS 91-20-3) Listed.  
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.  
Stoddard solvent (CAS 8052-41-3) Listed.  
White mineral oil (petroleum) (CAS 8042-47-5) Listed.

**US - Texas Effects Screening Levels: Listed substance**

Benzene, 1,2,4-trimethyl- (CAS 95-63-6) Listed.

Butene, homopolymer (CAS 9003-29-6) Listed.  
 Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.  
 Ethylbenzene (CAS 100-41-4) Listed.  
 Naphthalene (CAS 91-20-3) Listed.  
 Nonane (CAS 111-84-2) Listed.  
 Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.  
 Stoddard solvent (CAS 8052-41-3) Listed.  
 White mineral oil (petroleum) (CAS 8042-47-5) Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Ethylbenzene (CAS 100-41-4)

**US. Massachusetts RTK - Substance List**

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)  
 Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)  
 Ethylbenzene (CAS 100-41-4)  
 Naphthalene (CAS 91-20-3)  
 Nonane (CAS 111-84-2)  
 Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)  
 Stoddard solvent (CAS 8052-41-3)  
 White mineral oil (petroleum) (CAS 8042-47-5)

**US. New Jersey Worker and Community Right-to-Know Act**

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)  
 Ethylbenzene (CAS 100-41-4)  
 Naphthalene (CAS 91-20-3)  
 Nonane (CAS 111-84-2)  
 Stoddard solvent (CAS 8052-41-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)  
 Ethylbenzene (CAS 100-41-4)  
 Naphthalene (CAS 91-20-3)  
 Nonane (CAS 111-84-2)  
 Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)  
 Stoddard solvent (CAS 8052-41-3)  
 White mineral oil (petroleum) (CAS 8042-47-5)

**US. Rhode Island RTK**

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)  
 Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)  
 Ethylbenzene (CAS 100-41-4)  
 Naphthalene (CAS 91-20-3)  
 Nonane (CAS 111-84-2)  
 Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)  
 Stoddard solvent (CAS 8052-41-3)  
 White mineral oil (petroleum) (CAS 8042-47-5)

**US. California Proposition 65**



**WARNING:** This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer, and Ethylbenzene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Cumene (CAS 98-82-8) Listed: April 6, 2010  
 Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004  
 Naphthalene (CAS 91-20-3) Listed: April 19, 2002

**California Proposition 65 - CRT: Listed date/Developmental toxin**

Toluene (CAS 108-88-3) Listed: January 1, 1991

**Inventory status**


| Country(s) or region        | Inventory name                                | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada                      | Domestic Substances List (DSL)                | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)           | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other information

| LEGEND   |   |
|----------|---|
| Severe   | 4 |
| Serious  | 3 |
| Moderate | 2 |
| Slight   | 1 |
| Minimal  | 0 |

|                            |   |   |
|----------------------------|---|---|
| <b>HEALTH</b>              | * | 2 |
| <b>FLAMMABILITY</b>        |   | 2 |
| <b>PHYSICAL HAZARD</b>     |   | 0 |
| <b>PERSONAL PROTECTION</b> |   | X |



### Disclaimer

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

### Issue date

31-May-2021

### Version #

03

### Effective date

31-May-2021

### Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

### Further information

Not available.

### Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.