



SAFETY DATA SHEET

1. Identification

Product identifier	Transflo Dex VI
Other means of identification	Not available.
Recommended use	Lubricant
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	Irving Blending & Packaging
Address	555 Courtenay Bay Causeway Saint John NB E2L 4E6 Canada
Telephone	1.800.574.5823
E-mail	Not available.
Emergency phone number	1.800.424.9300 (CHEMTREC)
Supplier	See above.

2. Hazard identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
WHMIS 2015 defined hazards	Not classified
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	1-5*
Distillates (petroleum), hydrotreated light paraffinic		64742-55-8	1-5*
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		72623-86-0	60-80*

Chemical name	Common name and synonyms	CAS number	%
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based		72623-87-1	10-30*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Eye contact	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Ingestion	Rinse mouth with water, then drink one or two glasses of water. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemical. Water fog. Foam. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	May include and are not limited to: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep out of low areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Use care in handling/storage.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	1 mg/m3	Mist.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	1 mg/m3	Mist.
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (CAS 72623-87-1)	TWA	1 mg/m3	Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	15 minute	10 mg/m3	
	8 hour	5 mg/m3	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	15 minute	10 mg/m3	
	8 hour	5 mg/m3	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Safety glasses or goggles.

Skin protection**Hand protection**

Neoprene Gloves of nitrile rubber, PVA or Viton are recommended.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Chemical respirator with organic vapor cartridge.
Thermal hazards	Not applicable.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Red
Odor	Mild petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-59.8 °F (-51 °C)
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	424.4 °F (218.0 °C) Cleveland Open Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Insoluble
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	5.9 cSt @ 100°C 29.18 cSt @ 40°C
Other information	
Density	0.843 kg/l (15°C/59°F)

10. Stability and reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Keep away from extreme heat. Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents. Acids. Reducing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.

11. Toxicological information

Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.
---------------------------	---

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects**Acute toxicity**

Components	Species	Test Results
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.5 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	5000 mg/kg, ECHA
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (CAS 72623-87-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 hours, dust/mist
<i>Oral</i>		
LD50	Rat	5000 mg/kg, ECHA
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	

Recover days	Not available.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, NTP, or OSHA.
	Contains < 3% (w/w) DMSO-extract

ACGIH Carcinogens

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) A2 Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0) Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (CAS 72623-87-1) Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

US NTP Report on Carcinogens: Known carcinogen

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Known To Be Human Carcinogen.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Teratogenicity	Not available.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components	Species	Test Results
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (CAS 72623-87-1)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Listed.

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.

US - Minnesota Haz Subs: Listed substance

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Listed.

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.

US - Texas Effects Screening Levels: Listed substance

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Listed.

Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)
 Listed.
 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)
 Listed.

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

US. Rhode Island RTK

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

17-February-2021

Version #

01

Effective date

17-February-2021

Prepared by

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

Further information

Not available.

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.