

1. Identification

Product identifier	KLONDIKE Brake Clean - Aerosol	
Other means of identification		
Product code	Brake Clean - Aerosol	
Recommended use	Brake Parts Cleaner	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	KLONDIKE Lubricants Corporation	
Address	3078 275th Street Langley, BC V4W 3L4 Canada	
Telephone	General Information	1-877-293-4691
Website	www.klondikelubricants.com	
E-mail	info@klondikelubricants.com	
Emergency phone number	Chemtrec (Within US)	1-800-424-9300
	Chemtrec (International)	1-703-527-3887
Supplier	Refer to Manufacturer	

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	This mixture does not meet the classification criteria according to OSHA HazCom 2012.	
OSHA defined hazards	This mixture does not meet the classification criteria according to OSHA HazCom 2012.	
Label elements		



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves.
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. Other hazards which do not result in classification: Contact with liquefied gas might cause frostbites, in some cases with tissue damage. May cause respiratory irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Product may present an aspiration hazard, if ingested in large amounts. Prolonged or repeated exposure may cause kidney and central nervous system effects. Prolonged or repeated overexposure may cause liver effects.

Supplemental information

None.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Heptane	n-Heptane	142-82-5	90 - 100
Carbon Dioxide (gas)	CO2	124-38-9	1 - 5
Isopropanol	Dimethyl carbinol 2-Propanol Isopropyl alcohol Propan-2-ol	67-63-0	1 - 5

The exact concentrations of the above listed chemicals are being withheld as a trade secret as allowed by 29CFR1910.1200.

4. First-aid measures**Inhalation**

Move to fresh air. If breathing is difficult, give oxygen. If breathing stops, provide artificial respiration. Get medical attention if symptoms persist.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Duration of rinsing should be at least 15 minutes. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Wash contaminated clothing before reuse.

Eye contact

Rinse immediately with plenty of water for at least 15 minutes. Get medical attention if irritation persists after washing.

Ingestion

Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention.

Most important symptoms/effects, acute and delayed

May cause mild to moderate skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause moderate to severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing, and breathing difficulties. May cause central nervous system effects. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Product may present an aspiration hazard, if ingested in large amounts. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures**Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Firefighters should wear full protective gear. Ventilate the contaminated area. Remove all sources of ignition. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Hazardous combustion products

Carbon oxides. Other irritating fumes and smoke.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Vacuum up the spilled material. Stop the flow of material, if this is without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Vapors may form explosive mixtures with air. When using, do not eat, drink or smoke. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Use only in area provided with appropriate exhaust ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

CAUTION Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Keep away from heat, sparks and open flame. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon Dioxide (gas) (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Heptane (CAS 142-82-5)	PEL	2000 mg/m3 500 ppm
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3 400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Carbon Dioxide (gas) (CAS 124-38-9)	STEL	30000 ppm
Heptane (CAS 142-82-5)	TWA	5000 ppm
	STEL	500 ppm
Isopropanol (CAS 67-63-0)	TWA	400 ppm
	STEL	400 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Carbon Dioxide (gas) (CAS 124-38-9)	STEL	54000 mg/m3
		30000 ppm
	TWA	9000 mg/m3
Heptane (CAS 142-82-5)	Ceiling	5000 ppm
		1800 mg/m3
	TWA	440 ppm
Isopropanol (CAS 67-63-0)	TWA	350 mg/m3
		85 ppm
	STEL	1225 mg/m3
	TWA	500 ppm
		980 mg/m3
		400 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles). A full face shield may also be necessary. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves. Advice should be sought from glove suppliers.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Advice should be sought from respiratory protection specialists.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Material name: KLONDIKE Brake Clean - Aerosol
Brake Clean - Aerosol Version #: 01 Issue date: 03-10-2020

Physical state	Liquid.
Form	Clear liquid contained in pressurized aerosol can.
Color	Clear.
Odor	Alcohol-like.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-9.0 °C (15.8 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	45 hPa
Vapor density	3.5
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Percent volatile	100 %
Specific gravity	0.7

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not use in areas without adequate ventilation.
Incompatible materials	Strong oxidizing agents. Strong acids. Alkali metals.
Hazardous decomposition products	None known, refer to hazardous combustion products in Section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. May cause central nervous system effects.
Skin contact	May cause mild to moderate skin irritation.
Eye contact	May cause moderate to severe eye irritation.
Ingestion	May cause irritation of the gastrointestinal tract.

Most important symptoms/effects, acute and delayed

May cause mild to moderate skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause moderate to severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing, and breathing difficulties. May cause central nervous system effects. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Product may present an aspiration hazard, if ingested in large amounts. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Information on toxicological effects

Acute toxicity

This product is not classified as an acute toxicity hazard.
The below product data is the calculated ATE values for this mixture. Individual ingredient component data appears below the product mixture ATE values.

Product	Species	Test Results
KLONDIKE Brake Clean - Aerosol (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	3554.2 mg/kg
<i>Inhalation</i>		
LC50	Rat	1571.74 ppm, 4 hours (Vapor)
<i>Oral</i>		
LD50	Rat	14570.9 mg/kg
Components	Species	Test Results
Carbon Dioxide (gas) (CAS 124-38-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	Not applicable
<i>Inhalation</i>		
LC50	Rat	166170 ppm, 4 hours
<i>Oral</i>		
LD50	Rat	Not applicable
Heptane (CAS 142-82-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	3400 mg/kg
<i>Inhalation</i>		
LC50	Rat	102.5 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	> 15000 mg/kg
Isopropanol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12890 mg/kg
<i>Inhalation</i>		
LC50	Rat	17000 ppm, 4 hours (vapor) 41.8 mg/l, 4 hours (vapor)
<i>Oral</i>		
LD50	Rat	4720 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

May cause mild to moderate skin irritation.

Serious eye damage/eye irritation

May cause moderate to severe eye irritation.

Respiratory or skin sensitization

Respiratory sensitization This product is not expected to cause respiratory sensitization.

Skin sensitizer This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Specific Target Organ Toxicity (STOT), Single Exposure: Category 3
May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Not classified as a specific target organ toxicity -repeated exposure.

Aspiration toxicity Not expected to be an aspiration hazard.

Chronic effects Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Prolonged exposure may cause CNS (central nervous system) effects including dizziness, drowsiness and incoordination. Prolonged or repeated overexposure may cause liver and kidney effects.

12. Ecological information

Ecotoxicity See below for individual ingredient ecotoxicity data.

Components		Species	Test Results
Heptane (CAS 142-82-5)			
<i>Acute</i>			
	LC50	Rainbow trout (<i>Oncorhynchus mykiss</i>)	5.738 mg/l, 96 hours (QSAR Estimation)
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	4.338 mg/l, 72 Hours (QSAR Estimation)
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	1.5 mg/l, 48 Hours
Isopropanol (CAS 67-63-0)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	1400 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	9640 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Water flea (<i>Daphnia magna</i>)	30 mg/l, 21 days

* Estimates for product may be based on additional component data not shown.

Persistence and degradability Contains the following chemicals which are considered to be readily biodegradable: Heptane. Isopropyl alcohol. Hexane.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Heptane 4.66

Isopropanol 0.05

Bioconcentration factor (BCF)

Isopropanol 1

Mobility in soil The product itself has not been tested. Isopropyl alcohol evaporates quickly from soil due to its high vapor pressure, and is not expected to partition to the soil based on a calculated soil absorption coefficient (log Koc) of 0.03.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	This substance/mixture is not intended to be transported in bulk.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Heptane (CAS 142-82-5)

Listed.

Isopropanol (CAS 67-63-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Isopropanol	67-63-0	1 - 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Carbon Dioxide (gas) (CAS 124-38-9)
 Heptane (CAS 142-82-5)
 Isopropanol (CAS 67-63-0)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (gas) (CAS 124-38-9)
 Heptane (CAS 142-82-5)
 Isopropanol (CAS 67-63-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (gas) (CAS 124-38-9)
 Heptane (CAS 142-82-5)
 Isopropanol (CAS 67-63-0)

US. Rhode Island RTK

Isopropanol (CAS 67-63-0)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-10-2020

Version # 01

Disclaimer The information in this document was written based on the best knowledge and experience currently available, and is offered for your consideration and guidance when exposed to this product. KLONDIKE Lubricants Corporation disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this document does not apply to use with any other product or in any other process. This document may not be changed, or altered in any way without the expressed knowledge and permission of KLONDIKE Lubricants Corporation.

Bibliography Not available.