



## Safety Data Sheet

Copyright, 2022, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	10-2819-0	<b>Version number:</b>	1.01
<b>Issue Date:</b>	16/08/2022	<b>Supersedes date:</b>	04/04/2022

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Stainless Steel Cleaner & Polish

#### Product Identification Numbers

61-5000-6132-2      70-0713-1355-8

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Metal Polish, Cleans and polishes stainless steel, chrome, aluminum and laminated plastic surfaces.

#### 1.3. Supplier's details

**Address:** 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100  
**Telephone:** 080-45543000, contact Product EHS team  
**E Mail:** productehs.in@mmm.com  
**Website:** <http://solutions.3mindia.co.in>

#### 1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

### SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

#### 2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.

Specific Target Organ Toxicity (single exposure): Category 1.

#### 2.2. Label elements

##### Signal Word

Danger

##### Symbols

Flame | Health Hazard |

**Pictograms****HAZARD STATEMENTS:**

H222	Extremely flammable aerosol.
H229	Pressurised container. may burst if heated.
H370	Causes damage to organs: cardiovascular system.

**PRECAUTIONARY STATEMENTS****Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.

**Response:**

P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
-------------	--

**Storage:**

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.
-------------	--

**2.3. Other hazards**

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Water	7732-18-5	40 - 70
Mineral Oil	8042-47-5	10 - 30
Isobutane	75-28-5	7 - 13
Sorbitan oleate	1338-43-8	0.5 - 1.5

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. Get medical attention.

**Skin contact**

Wash with soap and water. If you feel unwell, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**SECTION 5: Fire-fighting measures**

**5.1. Suitable Extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide.

Carbon dioxide.

**Condition**

During combustion.

During combustion.

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidising agents.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
Natural gas	75-28-5	ACGIH	Limit value not established:	asphyxiant
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

**Skin/hand protection**

PPE No chemical protective gloves are required.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
----------------	---------

<b>Specific Physical Form:</b>	Aerosol
<b>Color</b>	White
<b>Odor</b>	Citrus
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	9 - 11
<b>Melting point/Freezing point: NA</b>	<i>Not applicable.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	> 100 °C
<b>Flash point</b>	No flash point
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapor Density and/or Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	0.95 g/ml
<b>Relative density</b>	0.92 - 0.98 [Ref Std: WATER=1]
<b>Water solubility</b>	Complete
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity/Kinematic Viscosity</b>	1,400 mPa-s - 4,500 mPa-s [Details:For Liquid]
<b>Volatile organic compounds (VOC)</b>	10 - 12 % weight [Test Method:calculated per CARB title 2]
<b>Percent volatile</b>	75 - 80 % weight
<b>VOC less H2O &amp; exempt solvents</b>	265 - 295 g/l [Test Method:calculated per CARB title 2]
<b>Molecular weight</b>	<i>No data available.</i>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Strong oxidising agents.

Strong acids.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May cause additional health effects (see below).

#### Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Additional Health Effects:

#### Single exposure may cause target organ effects:

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Sorbitan oleate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sorbitan oleate	Ingestion	Rat	LD50 > 39,800 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Mineral Oil	Rabbit	No significant irritation
Isobutane	Professional judgement	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
Mineral Oil	Rabbit	Mild irritant
Isobutane	Professional judgement	No significant irritation

**Sensitization:****Skin Sensitisation**

Name	Species	Value
Mineral Oil	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Mineral Oil	In Vitro	Not mutagenic
Isobutane	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Mineral Oil	Dermal	Mouse	Not carcinogenic
Mineral Oil	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral Oil	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks

**Aspiration Hazard**

Name	Value
Mineral Oil	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Mineral Oil	8042-47-5	Water flea	Estimated	48 hours	EL50	>100 mg/l
Mineral Oil	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
Mineral Oil	8042-47-5	Green algae	Estimated	72 hours	NOEL	100 mg/l
Mineral Oil	8042-47-5	Water flea	Estimated	21 days	NOEL	>100 mg/l
Isobutane	75-28-5		Data not available or insufficient for classification			N/A
Sorbitan oleate	1338-43-8	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Mineral Oil	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Isobutane	75-28-5	Experimental Photolysis		Photolytic half-life (in air)	13.4 days (t 1/2)	
Sorbitan oleate	1338-43-8	Estimated Biodegradation	28 days	BOD	68 % weight	OECD 301B - Modified sturm or CO2



**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Mineral Oil	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Isobutane	75-28-5	Experimental Bioconcentration		Log Kow	2.76	
Sorbitan oleate	1338-43-8	Estimated Bioconcentration		Bioaccumulation factor	7.8	

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other Adverse effects**

No information available.

The surfactant(s) contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans.

**SECTION 14: Transport Information****Air Transport (IATA) Regulations**

UN No UN1950

Proper Shipping Name AEROSOLS, FLAMMABLE

Hazard Class/Division 2.1

Subsidiary Risk Not applicable

Packing Group: Not applicable

**Marine Transport (IMDG)**

UN No UN1950

Proper Shipping Name AEROSOLS, FLAMMABLE

Hazard Class/Division 2.1

Subsidiary Risk Not applicable

Packing Group: Not applicable

Environmental Hazards: Not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**Applicable Environmental, Health and Safety Regulations**

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989  
Hazardous Waste(Management , Handling & Transboundary) Rules, 2008  
Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

Butane, all isomers

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

Product is classified as Very Highly Flammable (Aerosol).

**SECTION 16: Other information****NFPA Hazard Classification**

**Health:** 2    **Flammability:** 4    **Instability:** 0    **Special Hazards:** None  
**Aerosol Storage Code:** 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision information:**

Section 1: Product identification numbers information was modified.  
Section 09: Nanoparticle information was deleted.  
Section 12: Persistence and Degradability information information was modified.  
Section 12:Biocumulative potential information information was modified.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

**3M India SDSs are available at <http://solutions.3mindia.co.in>**