

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

SECTION 1. IDENTIFICATION

Product name : P30 PLUS, Anti-hologram polish, 997 mL
Product code : 893.150930
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Polish

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 4

GHS label elements

Signal Word : Warning
Hazard Statements : H227 Combustible liquid.
Precautionary Statements : **Prevention:**

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
 Date of first issue: 05/16/2012

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves, protective clothing, eye protection and face protection.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	No data available	90622-58-5	$\geq 10 - < 30$ *
White mineral oil (petroleum)	Paraffin oil	8042-47-5	$\geq 5 - < 10$ *
Aluminum oxide	Dialuminum trioxide	1344-28-1	$\geq 5 - < 10$ *
Glycerine	1,2,3-Propanetriol	56-81-5	$\geq 1 - < 5$ *
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No data available	64742-65-0	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

oil barriers).
 Retain and dispose of contaminated wash water.
 Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
 Soak up with inert absorbent material.
 Suppress (knock down) gases/vapors/mists with a water spray jet.
 For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
 Avoid breathing vapors.
 Do not swallow.
 Avoid contact with eyes.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep container tightly closed.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Explosives
 Gases

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
 Date of first issue: 05/16/2012

Recommended storage temperature : 15 - 25 °C

Storage period : 24 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
Aluminum oxide	1344-28-1	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA	10 mg/m ³	CA AB OEL
		TWAEV (total dust)	10 mg/m ³ (Aluminum)	CA QC OEL
		TWA (Respirable)	1 mg/m ³ (Aluminum)	CA BC OEL
		TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH
Glycerine	56-81-5	TWA (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	10 mg/m ³	CA BC OEL
		TWA (Respirable mist)	3 mg/m ³	CA BC OEL
		TWAEV (Mist)	10 mg/m ³	CA QC OEL
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
TWA (Inhalable particulate matter)		5 mg/m ³	ACGIH	

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the re-

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

commended guidelines, use respiratory protection.

- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Latex gloves
- Break through time : 240 min
- Glove thickness : 0.25 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : gray
- Odor : characteristic
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

Initial boiling point and boiling range	:	100 °C
Flash point	:	> 90 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	0.5 %(V)
Vapor pressure	:	0.6 hPa (20 °C)
Relative vapor density	:	No data available
Density	:	0.99 g/cm ³
Solubility(ies)	:	
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	8,000 - 13,000 mPa.s (20 °C)
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac-	:	Combustible liquid.

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

tions		Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 4,951 mg/l Exposure time: 4 h Test atmosphere: vapor Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 3,160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Aluminum oxide:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
---------------------	---	---------------------------

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Glycerine:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity : LD50 (Guinea pig): > 5,000 mg/kg

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Species : Rabbit
Result : Mild skin irritation
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.
Remarks : Based on data from similar materials

White mineral oil (petroleum):

Species : Rabbit
Result : No skin irritation

Aluminum oxide:

Species : Rabbit
Result : No skin irritation

Glycerine:

Species : Rabbit
Result : No skin irritation

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation

Aluminum oxide:

Species : Rabbit
Result : No eye irritation

Glycerine:

Species : Rabbit
Result : No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

White mineral oil (petroleum):

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Aluminum oxide:

Test Type : Draize Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Routes of exposure : Inhalation
Species : Mouse
Result : negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

Aluminum oxide:

- Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Glycerine:

- Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
- Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Test Type: Chromosome aberration test in vitro
Result: negative
- Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

- Species : Rat
Application Route : inhalation (vapor)
Exposure time : 105 weeks
Result : negative

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

Remarks : Based on data from similar materials

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

Aluminum oxide:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 6- 12 Months
Result : negative
Remarks : Based on data from similar materials

Glycerine:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Aluminum oxide:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Glycerine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:**Aluminum oxide:**

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Species : Rat
NOAEL : > 10,400 mg/m³
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

P30 PLUS, Anti-hologram polish, 997 mL

Version Revision Date: SDS Number: Date of last issue: 11/10/2022
5.6 05/15/2023 11005421-00009 Date of first issue: 05/16/2012

White mineral oil (petroleum):

Species : Rat
LOAEL : > 160 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
LOAEL : >= 1 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks
Method : OECD Test Guideline 412

Aluminum oxide:

Species : Rat
NOAEL : 0.07 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 6 Months

Glycerine:

Species : Rat
NOAEL : 0.167 mg/l
LOAEL : 0.622 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 8,000 - 10,000 mg/kg
Application Route : Ingestion
Exposure time : 2 y

Species : Rabbit
NOAEL : 5,040 mg/kg
Application Route : Skin contact
Exposure time : 45 Weeks

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 980 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks
Remarks : Based on data from similar materials

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

Aspiration toxicity

Not classified based on available information.

Components:**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.

White mineral oil (petroleum):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
-

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 21 d

Aluminum oxide:
Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Glycerine:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 54,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,955 mg/l
Exposure time: 48 h

Toxicity to microorganisms : NOEC (Pseudomonas putida): > 10,000 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

P30 PLUS, Anti-hologram polish, 997 mL

Version 5.6 Revision Date: 05/15/2023 SDS Number: 11005421-00009 Date of last issue: 11/10/2022
Date of first issue: 05/16/2012

Persistence and degradability**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31.3 %
Exposure time: 28 d
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Glycerine:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 30 d
Method: OECD Test Guideline 301D

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Components:****Glycerine:**

Partition coefficient: n-octanol/water : log Pow: -1.75

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 13.51 % / 133.72 g/l
Remarks: VOC content excluding water and exempt compounds

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	05/15/2023
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

P30 PLUS, Anti-hologram polish, 997 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
5.6	05/15/2023	11005421-00009	Date of first issue: 05/16/2012

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8