

**P55 PLUS, Universal polish, 1050 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

---

**SECTION 1. IDENTIFICATION**

Product name : P55 PLUS, Universal polish, 1050 mL

Product code : 893.150955

Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Polish

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 4

Skin sensitization : Category 1

**GHS label elements**

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
 Date of first issue: 05/16/2012

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H227 Combustible liquid.  
 H317 May cause an allergic skin reaction.

Precautionary Statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapors.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

Vapors may form explosive mixture with air.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	No data available	90622-58-5	>= 10 - < 30 *
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10 *
Aluminum oxide	Dialuminum trioxide	1344-28-1	>= 5 - < 10 *
White mineral oil (petroleum)	Paraffin oil	8042-47-5	>= 1 - < 5 *
Sweet orange pulp extract	CITRUS AURANTIUM	8028-48-6	>= 0.1 - < 1 *

**P55 PLUS, Universal polish, 1050 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

	DULCIS PEEL EXTRACT		
--	------------------------	--	--

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

**P55 PLUS, Universal polish, 1050 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

---

- Hazardous combustion products : Carbon oxides  
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
-

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
 Date of first issue: 05/16/2012

Avoid breathing vapors.  
 Do not swallow.  
 Avoid contact with eyes.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Keep container tightly closed.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Take precautionary measures against static discharges.  
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
 Keep tightly closed.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents  
 Explosives  
 Gases

Recommended storage temperature : 15 - 25 °C

Further information on storage stability : Protect from frost.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-47-8	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA AB OEL
		TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	525 mg/m <sup>3</sup>	CA ON OEL
Aluminum oxide	1344-28-1	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup> (Aluminum)	CA QC OEL
		TWA (Respirable)	1 mg/m <sup>3</sup> (Aluminum)	CA BC OEL

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
 Date of first issue: 05/16/2012

		TWA (Respirable particulate matter)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

**Hand protection**

Material : Latex gloves  
 Break through time : 240 min  
 Glove thickness : 0.25 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
 Wear the following personal protective equipment:  
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
 When using do not eat, drink or smoke.

**P55 PLUS, Universal polish, 1050 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

---

Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	paste
Color	:	orange
Odor	:	fruity
Odor Threshold	:	No data available
pH	:	7.8 (20 °C)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	100 °C
Flash point	:	82 °C
		Method: ISO 2719
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapor pressure	:	0.4 hPa (20 °C)
Relative vapor density	:	No data available
Density	:	0.91 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	> 200 °C

**P55 PLUS, Universal polish, 1050 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

---

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 8,000 - 13,000 mPa.s ( 20 °C)

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Combustible liquid.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Remarks: Based on data from similar materials

---



**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Based on data from similar materials

**Aluminum oxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

**White mineral oil (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Sweet orange pulp extract:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Species : Rabbit  
Result : Mild skin irritation  
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.  
Remarks : Based on data from similar materials

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.

**Aluminum oxide:**

Species : Rabbit  
Result : No skin irritation

**White mineral oil (petroleum):**

Species : Rabbit  
Result : No skin irritation

**Sweet orange pulp extract:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Aluminum oxide:**

Species : Rabbit  
Result : No eye irritation

**White mineral oil (petroleum):**

Species : Rabbit  
Result : No eye irritation

**Sweet orange pulp extract:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Aluminum oxide:**

Test Type : Draize Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

Routes of exposure : Inhalation  
Species : Mouse  
Result : negative

**White mineral oil (petroleum):**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**Sweet orange pulp extract:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : positive  
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

**Germ cell mutagenicity**

Not classified based on available information.

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

**Aluminum oxide:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

**White mineral oil (petroleum):**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Sweet orange pulp extract:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

**Carcinogenicity**

Not classified based on available information.

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 105 weeks  
Result : negative  
Remarks : Based on data from similar materials

**Aluminum oxide:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 6- 12 Months  
Result : negative  
Remarks : Based on data from similar materials

**White mineral oil (petroleum):**

Species : Rat  
Application Route : Ingestion  
Exposure time : 24 Months  
Result : negative

**Sweet orange pulp extract:**

Species : Mouse  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Aluminum oxide:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

**White mineral oil (petroleum):**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Skin contact  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Components:****Aluminum oxide:**

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**Sweet orange pulp extract:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Repeated dose toxicity****Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Species : Rat  
NOAEL : > 10,400 mg/m<sup>3</sup>

**P55 PLUS, Universal polish, 1050 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

---

Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

**Aluminum oxide:**

Species : Rat  
NOAEL : 0.07 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 6 Months

**White mineral oil (petroleum):**

Species : Rat  
LOAEL : > 160 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
LOAEL : >= 1 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 412

**Sweet orange pulp extract:**

Species : Rat  
NOAEL : 5 mg/kg  
LOAEL : 30 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

**Aspiration toxicity**

Not classified based on available information.

**Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**White mineral oil (petroleum):**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Sweet orange pulp extract:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 1 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials  
No toxicity at the limit of solubility.

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics ,<2% aromatics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201



**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

**Aluminum oxide:****Ecotoxicology Assessment**

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**White mineral oil (petroleum):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l  
Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l  
Exposure time: 21 d

**Sweet orange pulp extract:**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): 5.65 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.1 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): 150 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

**Persistence and degradability****Components:****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31.3 %  
Exposure time: 28 d  
Remarks: Based on data from similar materials

**Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

**P55 PLUS, Universal polish, 1050 mL**

Version 9.1      Revision Date: 10/21/2021      SDS Number: 1447383-00005      Date of last issue: 10/08/2020  
Date of first issue: 05/16/2012

---

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 69 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**White mineral oil (petroleum):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d

**Sweet orange pulp extract:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83.4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**Bioaccumulative potential****Components:****Sweet orange pulp extract:**

Partition coefficient: n-octanol/water : log Pow: > 4

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

## P55 PLUS, Universal polish, 1050 mL

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

### TDG

Not regulated as a dangerous good

### Special precautions for user

Not applicable

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 15 % / 142 g/l

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with

**P55 PLUS, Universal polish, 1050 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 10/08/2020
9.1	10/21/2021	1447383-00005	Date of first issue: 05/16/2012

---

x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/21/2021  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8