

HIT-RE 500 V3

en	This safety data sheet file is issued for the following production lots: 1. Version 2.4 is valid for HIT-RE 500 V3 with a maximum expiration date of 12/2024 (see foil pack manifold) 2. Version 3.0 is valid for HIT-RE 500 V3 with a minimum expiration date of 01/2025 (see the foil pack manifold)
de	Diese Sicherheitsdatenblatt-Datei betrifft die folgenden Fertigungslose: 1. Version 2.4 ist gültig für HIT-RE 500 V3 mit einem Haltbarkeitsdatum bis 12/2024 (siehe Verbindungsteil) 2. Version 3.0 ist gültig für HIT-RE 500 V3 mit einem Haltbarkeitsdatum ab 01/2025 (siehe Verbindungsteil)
nl	Dit veiligheidsinformatiebladbestand wordt afgegeven voor de volgende productie-lots: 1. Versie 2.4 is geldig voor HIT-RE 500 V3 met een maximale houdbaarheidsdatum tot 12/2024 (zie foliepak verdeler) 2. Versie 3.0 is geldig voor HIT-RE 500 V3 met een minimale houdbaarheidsdatum tot 01/2025 (zie foliepak verdeler)
fr	Ce fichier de données de sécurité est délivré pour les lots de production suivants : 1. La version 2.4 est valide pour HIT-RE 500 V3 avec une date d'expiration maximale de 12/2024 (voir le raccord de cartouche souple) 2. La version 3.0 est valide pour HIT-RE 500 V3 avec une date d'expiration maximale de 01/2025 (voir le raccord de cartouche souple)
da	Denne sikkerhedsdatabladsfil er udgivet for følgende produktions lots: 1. Version 2.4 er gældende for HIT-RE 500 V3 med en maksimal udløbsdato d. 12/2024 (se foliepakkens manifold) 2. Version 3.0 er gældende for HIT-RE 500 V3 med en mindste udløbsdato d. 01/2025 (se foliepakkens manifold)
sv	Denna säkerhetsdatabladsfil har utfärdats för följande tillverkningspartier: 1. Version 2.4 är giltig för HIT-RE 500 V3 med ett sista giltighetsdatum den 12/2024 (se folieförpackningens grenrör) 2. Version 3.0 är giltig för HIT-RE 500 V3 med ett första giltighetsdatum den 01/2025 (se folieförpackningens grenrör)
fi	Tämä käyttöturvallisuustiedote koskee seuraavia tuotantoeriä: 1. Versio 2.4 koskee HIT-RE 500 V3 -tuotetta, jonka viimeinen käyttöpäivämäärä on 12/2024 tai sitä ennen (ks. foliopakkauksen taite) 2. Versio 3.0 koskee HIT-RE 500 V3 -tuotetta, jonka viimeinen käyttöpäivämäärä on 01/2025 tai sen jälkeen (ks. foliopakkauksen taite)
hu	Ezt a biztonsági adatlapot a következő gyártási tételekhez bocsátják ki: 1. Az 2.4 változat legfeljebb 2024/12 lejáratú dátummal érvényes a HIT-RE 500 V3-re (lásd a fóliacsomag sokszorosított iratát) 2. Az 3.0 változat legalább 2025/01 lejáratú dátummal érvényes a HIT-RE 500 V3-re (lásd a fóliacsomag sokszorosított iratát)
es	Este archivo de hoja de datos de seguridad se emite para los siguientes lotes de producción: 1. Versión 2.4 válida para HIT-RE 500 V3 con una fecha de caducidad máxima de 12/2024 (consulte el colector de láminas) 2. Versión 3.0 válida para HIT-RE 500 V3 con una fecha de caducidad mínima de 01/2025 (consulte el colector de láminas)
pt	Este ficheiro com ficha de dados de segurança é emitido para os seguintes lotes de produção: 1. A versão 2.4 é válida para a HIT-RE 500 V3 com um prazo máximo de validade até 12/2024 (ver as diversas embalagens) 2. A versão 3.0 é válida para a HIT-RE 500 V3 com um prazo mínimo de validade até 01/2025 (ver as diversas embalagens)
it	Questo file della scheda tecnica di sicurezza è rilasciato per i seguenti lotti di produzione: 1. La versione 2.4 è valida per HIT-RE 500 V3 con data di scadenza massima 12/2024 (vedere la giunzione della confezione) 2. La versione 3.0 è valida per HIT-RE 500 V3 con data di scadenza minima 01/2025 (vedere la giunzione della confezione)
pl	Ten plik arkusza danych bezpieczeństwa jest wydany dla następujących części produkcyjnych: 1. Wersja 2.4 obowiązuje w przypadku HIT-RE 500 V3 z maksymalnym dniem rozpoczęcia pracy 12/2024 (patrz opakowanie foliowe) 2. Wersja 3.0 obowiązuje w przypadku HIT-RE 500 V3 z minimalnym dniem rozpoczęcia pracy 01/2025 (patrz opakowanie foliowe)
ru	Этот файл сертификата безопасности предоставлен для следующих партий продукции: 1. Версия 2.4 действительна для HIT-RE 500 V3 с максимальным сроком годности до 12.2024 г. (см. присоединительную часть на капсуле) 2. Версия 3.0 действительна HIT-RE 500 V3 с минимальным сроком годности до 01.2025 г. (см. присоединительную часть на капсуле)
el	Το παρόν δελτίο δεδομένων ασφαλείας εκδίδεται για τις ακόλουθες παρτίδες παραγωγής: 1. Η έκδοση 2.4 ισχύει για το HIT-RE 500 V3 με μέγιστη ημερομηνία λήξης τον 12/2024 (βλέπε διανομέα συσκευασίας μεμβράνης) 2. Η έκδοση 3.0 ισχύει για το HIT-RE 500 V3 με ελάχιστη ημερομηνία λήξης τον 01/2025 (βλέπε τον διανομέα της συσκευασίας μεμβράνης)
cs	Tento soubor s bezpečnostním listem je vystaven pro tyto výrobní závody 1. Verze 2.4 je platná pro HIT-RE 500 V3 s maximálním datem expirace 12/2024 (viz fólie balení) 2. Verze 3.0 je platná pro HIT-RE 500 V3 s minimálním datem expirace 01/2025 (viz fólie balení)
bg	Този информационен лист за безопасност се публикува за следните производствени партии: 1. Версия 2.4 е валидна за HIT-RE 500 V3 с максимален срок на валидност до 12.2024 г. (вж. фолийна опаковка за колектор) 2. Версия 3.0 е валидна за HIT-RE 500 V3 с минимален срок на изтичане 01.2025 г. (вж. фолийна опаковка за колектор)
lv	Šo drošības datu lapa ir izsniegta šādām ražojumu partijām: 1. Versija 2.4 ir derīga izstrādājumam HIT-RE 500 V3, kura maksimālais derīguma termiņš ir 2024. gada maijs (skatīt folija iepakojuma kolektoru) 2. Versija 3.0 ir derīga izstrādājumam HIT-RE 500 V3, kura minimālais derīguma termiņš ir 2025. gada jūnijs (skatīt folija iepakojuma kolektoru)
lt	Šis saugos duomenų lapo failas išduodamas šioms gamybos partijoms: 1. 2.4 versija galioja HIT-RE 500 V3, kurios maksimali galiojimo data – 2024-12 (žr. folinių pakuočių rinkinį) 2. 3.0 versija galioja HIT-RE 500 V3, kurios minimali galiojimo data – 2025-01 (žr. folinių pakuočių rinkinį)
sk	Tento súbor bezpečnostných údajov sa vydáva pre tieto výrobné šarže: 1. Verzia 2.4 je platná pre HIT-RE 500 V3 s maximálnym dátumom expirácie 12/2024 (pozrite si údaj na fólii balenia) 2. Verzia 3.0 je platná pre HIT-RE 500 V3 s minimálnym dátumom expirácie 01/2025 (pozrite si údaj na fólii balenia)
sl	Datoteka z varnostnim listom je izdana za naslednje proizvodne serije: 1. Različica 2.4 je veljavna za izdelek HIT-RE 500 V3 z maksimalnim datumom poteka veljavnosti: 12/2024 (glejte pakiranje) 2. Različica 3.0 je veljavna za izdelek HIT-RE 500 V3 z minimalnim datumom poteka veljavnosti: 01/2025 (glejte pakiranje)

HIT-RE 500 V3

et	See ohutuskaardi fail on välja antud järgmistele tootepartidele: 1. Versioon 2.4 kehtib tootele HIT-RE 500 V3 viimase säilimiskuupäevaga 12/2024 (vt fooliumpakendi hargnemiskohta) 2. Versioon 3.0 kehtib tootele HIT-RE 500 V3 esimese säilimiskuupäevaga 01/2025 (vt fooliumpakendi hargnemiskohta)
ro	Acest fișier cu date tehnice de securitate este emis pentru următoarele locuri de producție: 1. Versiunea 2.4 este valabilă pentru HIT-RE 500 V3 cu data maximă de expirare 12/2024 (a se vedea racordul pentru cartușe din folie) 2. Versiunea 3.0 este valabilă pentru HIT-RE 500 V3 cu data minimă de expirare 01/2025 (a se vedea racordul pentru cartușe din folie)
hr	Ovaj sigurnosno-tehnički list izdaje se za sljedeće proizvodne serije: 1. Verzija 2.4 vrijedi za HIT-RE 500 V3 s maksimalnim rokom trajanja do 12/2024 (vidjeti razvodnik iz folije) 2. Verzija 3.0 vrijedi za HIT-RE 500 V3 s minimalnim rokom trajanja do 01/2025 (vidjeti razvodnik iz folije)
tr	Bu güvenlik bilgi formu dosyası aşağıdaki üretim partileri için hazırlanmıştır: 1. Versiyon 2.4, maksimum son kullanma tarihi 12/2024 olan HIT-RE 500 V3 için geçerlidir (bkz. folyo paketi manifoldu) 2. Versiyon 3.0, inimum son kullanma tarihi 01/2025 olan HIT-RE 500 V3 için geçerlidir (bkz. folyo paketi manifoldu)
uk	Цей файл сертифіката безпеки надано для наступних партій продукції: 1. Версія 2.4 дійсна для HIT-RE 500 V3 з максимальним терміном придатності до 12.2024 р. (див. приєднувальну частину на капсулі) 2. Версія 3.0 дійсна для HIT-RE 500 V3 з мінімальним терміном придатності до 01.2025 р. (див. приєднувальну частину на капсулі)
zh	本安全数据表文件针对以下生产批次发布： 1. 版本 2.4 对 HIT-RE 500 V3 有效，最长失效日期为 2024 年 12 月（参见箔包装歧管） 2. 版本 3.0 对 HIT-RE 500 V3 有效，最短失效日期为 2025 年 1 月（参见箔包装歧管）
ar	يتم إصدار ملف صحيفة بيانات السلامة لتشغيلات الإنتاج التالية: 1. الإصدار 2.4 صالح لـ HIT-RE 500 V3 بعد أقصى لتاريخ انتهاء الصلاحية هو 2024/12 (انظر العبوة المصنوعة من رقائق الألومنيوم) 2. الإصدار 3.0 صالح لـ HIT-RE 500 V3 على الأقل لتاريخ انتهاء الصلاحية هو 2025/1 (انظر العبوة المصنوعة من رقائق الألومنيوم)
ja	この安全性データシートファイルは、次の生産ロット用に発行されています： 1. バージョン 2.4 は、有効期限が最大 2024 年 12 月までの HIT-RE 500 V3 に対して有効です (フویلパック連結部に表示) 2. バージョン 3.0 は、有効期限が 2025 年 1 月以降の HIT-RE 500 V3 に対して有効です (フویلパック連結部に表示)
sr	Datoteka bezbednosnog lista se izdaje za sledeće proizvodne serije: 1. Verzija 2.4 je dostupna za HIT-RE 500 V3 sa maksimalnim datumom isteka 12/2024 (pogledajte ivicu pakovanja od folije) 2. Verzija 3.0 je dostupna za HIT-RE 500 V3 sa minimalnim datumom isteka 01/2025 (pogledajte ivicu pakovanja od folije)
ms	Fail helaian data keselamatan ini dikeluarkan untuk lot pengeluaran yang berikut: 1. Versi 2.4 adalah sah untuk HIT-RE 500 V3 dengan tarikh tamat tempoh maksimum pada 12/2024 (lihat manifold pek kerajang) 2. Versi 3.0 adalah sah untuk HIT-RE 500 V3 dengan tarikh tamat tempoh minimum pada 01/2025 (lihat manifold pek kerajang)
ko	본 안전보건자료는 다음 제품 로트에 대해 발급되었습니다. 1. 버전 2.4(은)는 HIT-RE 500 V3에 대해 유효하며, 최대 만료 기한은 2024년 12월입니다(호일 팩 매니폴드 참조) 2. 버전 3.0(은)는 HIT-RE 500 V3에 대해 유효하며, 최소 만료 기한은 2025년 1월입니다(호일 팩 매니폴드 참조)
id	File lembar data keselamatan ini diterbitkan untuk lot produksi berikut: 1. Versi 2.4 berlaku untuk HIT-RE 500 V3 dengan tanggal kedaluwarsa maksimum 12/2024 (lihat foil pack manifold) 2. Versi 3.0 berlaku untuk HIT-RE 500 V3 dengan tanggal kedaluwarsa minimum 01/2025 (lihat foil pack manifold)
he	קובץ גיליון נתוני בטיחות זה מונפק עבור מגרשי הייצור הבאים: 1. גרסה 2.4 תקפה ל-HIT-RE 500 V3 עם תאריך תפוגה מקסימלי של 12/2024 (ראה יריעת פאק מניפולד) 2. גרסה 3.0 תקפה ל-HIT-RE 500 V3 עם תאריך תפוגה מינימלי של 01/2025 (ראה יריעת פאק מניפולד)
th	แผนข้อมูลด้านความปลอดภัยนี้จัดทำสำหรับล็อตการผลิตดังต่อไปนี้: 1. เวอร์ชัน 2.4 ใช้ได้กับ HIT-RE 500 V3 ที่มีวันหมดอายุไม่เกิน 12/2024 (โปรดดูแผ่นพับห่อฟอยล์) 2. เวอร์ชัน 3.0 ใช้ได้กับ HIT-RE 500 V3 ที่มีวันหมดอายุขั้นต่ำ 01/2025 (โปรดดูแผ่นพับห่อฟอยล์)
vi	Tập bảng dữ liệu an toàn này được phát hành cho các lô sản xuất sau: 1. Phiên bản 2.4 hợp lệ cho HIT-RE 500 V3 với ngày hết hạn tối đa là 12/2024 (xem ống keo cấy thép) 2. Phiên bản 3.0 hợp lệ cho HIT-RE 500 V3 với ngày hết hạn tối thiểu là 01/2025 (xem ống keo cấy thép)
zh tw	下列生產批次將獲核發本安全資料表檔案： 1. 2.4 版適用於 HIT-RE 500 V3，最長到期日 12/2024 (請見鋁箔包打字紙) 2. 3.0 版適用於 HIT-RE 500 V3，最短到期日 01/2025 (請見鋁箔包打字紙)
kk	Бұл қауіпсіздік паспорты мына өндірістік партиялар үшін шығарылады: 1. 2.4 нұсқасы жарамдылық мерзімі көп уақытты (12/2024) қамтитын HIT-RE 500 V3 үшін жарамды (жұқалтыр қаптаманы қараңыз) 2. 3.0 нұсқасы жарамдылық мерзімі аз уақытты (01/2025) қамтитын HIT-RE 500 V3 үшін жарамды (жұқалтыр қаптаманы қараңыз)

HIT-RE 500 V3

Safety information for 2-Component-products

Issue date: 08/12/2022

Revision date: 08/12/2022

Supersedes: 13/05/2020

Version: 3.0

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-RE 500 V3



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification (GHS CA)

Skin corrosion/irritation, Category 1B

H314

Skin sensitisation, Category 1

H317

Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

H335

Label elements

GHS CA labelling

Hazard pictograms (GHS CA)



GHS05



GHS07

Signal word (GHS CA)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS CA)

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H335 - May cause respiratory irritation.

HIT-RE 500 V3

Safety information for 2-Component-products

Precautionary statements (GHS CA)


P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

Additional information

2-component-foilpack, contains:

Component A: Epoxy resin, Reactive diluent, inorganic filler

Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	Classification (GHS CA)
HIT-RE 500 V3, B		1	pcs (pieces)	Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335
HIT-RE 500 V3, A		1	pcs (pieces)	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters
Notify authorities if liquid enters sewers or public waters
Avoid release to the environment
Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.
After curing, the product can be disposed of with household waste.

Storage conditions

Protect from sunlight. Store in a well-ventilated place.

Technical measures

Comply with applicable regulations

Precautions for safe handling

Wear personal protective equipment
Avoid contact with skin and eyes
Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
Avoid contact during pregnancy/while nursing

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation
Mechanically recover the product
On land, sweep or shovel into suitable containers
Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition
Direct sunlight

Incompatible products

Strong bases
Strong acids

HIT-RE 500 V3

Safety information for 2-Component-products

SECTION 6: First aid measures

First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after ingestion	Do not induce vomiting Rinse mouth Immediately call a POISON CENTER/doctor.
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures general	Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	Causes serious eye damage.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Other medical advice or treatment	Treat symptomatically

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)
Issue date: 12/08/2022

Revision date: 12/08/2022

Supersedes: 05/13/2020

Version: 3.0

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500 V3, A
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.3. Supplier

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
Mississauga, Ontario, L5N 6S2
Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
Kaufering, 86916
Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec
	Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada)
	Tel.: 703 527 3887 (Other countries)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Danger

Hazard statements (GHS CA)

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	25 – 40	Carc. 1A, H350
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane / 2,2-bis(4-(2,3-epoxypropyloxy)phenyl)propane / 2,2-bis(4-glycidyloxyphenyl)propane	CAS-No.: 1675-54-3	25 – 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	-	CAS-No.: 9003-36-5	10 – 20	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Trimethylol ethane triglycidyl ether Polymer	-	CAS-No.: 68460-21-9	5 – 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
butanedioldiglycidyl ether	1,4-bis(2,3-epoxypropoxy)butane; butanedioldiglycidyl ether / 1,4-bis(2,3-epoxypropoxy)butane / 1,4-bis(2,3-epoxypropoxy)butane	CAS-No.: 2425-79-8	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	((3-(trimethoxysilyl)propoxy)methyl)oxirane / [3-(2,3-epoxypropoxy)propyl]trimethoxysilane / 1-(glycidyloxy)-3-(trimethoxysilyl)propane	CAS-No.: 2530-83-8	2.5 – 5	Eye Dam. 1, H318 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
---------------------------	---



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Protection during firefighting

Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Spilled material may present a slipping hazard.

6.2. Methods and materials for containment and cleaning up

For containment

Collect spillage.

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.

Other information

Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Protect from sunlight.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Heat and ignition sources

Keep away from heat and direct sunlight.

Storage temperature

5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure adequate ventilation.

Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Materials for protective clothing:

Long sleeved protective clothing

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4	

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	No data available
pH	6.6
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.45 g/cm³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Viscosity, kinematic	No data available
Viscosity, dynamic	45 – 59 Pa·s 23 °C
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 oral	11400 mg/kg
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)

butanedioldiglycidyl ether (2425-79-8)	
LD50 oral rat	2980 mg/kg (Rat)
LD50 oral	1163 mg/kg (Rat; Exp. Key study ECHA)
LD50 dermal rabbit	1130 mg/kg (Rabbit)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)

Skin corrosion/irritation	Causes skin irritation. pH: 6.6
Serious eye damage/irritation	Causes serious eye damage. pH: 6.6
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Carcinogenicity	Not classified
Quartz (SiO ₂) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LC50 - Fish [1]	1.2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
LC50 - Fish [2]	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
Threshold limit - Algae [1]	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit - Algae [2]	4.2 mg/l (72 h; Scenedesmus sp.)
butanedioldiglycidyl ether (2425-79-8)	
LC50 - Fish [1]	24 mg/l (96 h; Pisces) ECHA
LC50 - Other aquatic organisms [1]	> 160 mg/l
NOEC (acute)	40 mg/l
Threshold limit - Algae [1]	88930 mg/l (96 h; Algae)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LC50 - Fish [1]	55 mg/l (96 h; Cyprinus carpio; Young)
LC50 - Fish [2]	237 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 - Crustacea [1]	473 – 710 mg/l (48 h; Daphnia magna)



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Threshold limit - Algae [1]	119 mg/l (7 days; <i>Anabaena flosaquae</i>)
Threshold limit - Algae [2]	250 mg/l (72 h; <i>Selenastrum capricornutum</i>)

12.2. Persistence and degradability

HIT-RE 500 V3, A	
Persistence and degradability	May cause long-term adverse effects in the environment.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
butanedioldiglycidyl ether (2425-79-8)	
Biochemical oxygen demand (BOD)	0.01982 g O ₂ /g substance

12.3. Bioaccumulative potential

HIT-RE 500 V3, A	
Bioaccumulative potential	Not established.
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
butanedioldiglycidyl ether (2425-79-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.15
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)

12.4. Mobility in soil

Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Ecology - soil	No (test) data on mobility of the substance available.
butanedioldiglycidyl ether (2425-79-8)	



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
Special provision(s) applied : 375	Special provision(s) applied : 969	Special provision(s) applied : A197	Special provision(s) applied : 375
These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.			
14.1. UN number or ID number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Environmentally hazardous substance, solid, n.o.s. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
Transport document description			
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III	UN 3077 Environmentally hazardous substance, solid, n.o.s. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III
14.3. Transport hazard class(es)			
9	9	9	9

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ADR	IMDG	IATA	RID
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg). The environmentally hazardous substance mark is therefore not required, as stated in the ADR regulation, section 5.2.1.8.1.			
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M7
Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR)

-

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23
MFAG-No	171

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg
Packing instructions (RID)	P002, IBC08, LP02, R001



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-RE 500 V3, A

Canada DSL NDSL Flags

All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)

Listed on the Canadian DSL (Domestic Substances List)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)

Listed on the Canadian DSL (Domestic Substances List)

butanedioldiglycidyl ether (2425-79-8)

Listed on the Canadian DSL (Domestic Substances List)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

SDS Major/Minor	None
Issue date	12-08-2022
Revision date	12-08-2022
Supersedes	05-13-2020

Indication of changes			
Section	Changed item	Change	Comments
2.1	Classification (GHS CA)	Modified	
2.2	Hazard pictograms (GHS CA)	Modified	
2.2	Hazard statements (GHS CA)	Modified	
3.2	Composition/information on ingredients	Modified	
14	Transport information	Modified	

Other information None.



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of H-statements:	
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
EC50	Median effective concentration
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

SDS_CA_Hilti



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 12/08/2022

Revision date: 12/08/2022

Supersedes: 05/13/2020

Version: 1.5

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500 V3, B
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.3. Supplier

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
Mississauga, Ontario, L5N 6S2
Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
Kaufering, 86916
Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec
	Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada)
	Tel.: 703 527 3887 (Other countries)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin corrosion/irritation, Category 1B	H314	Causes severe skin burns and eye damage.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3,	H335	May cause respiratory irritation.
Respiratory tract irritation		
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Danger

Hazard statements (GHS CA)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H335 - May cause respiratory irritation.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
2-methyl-1,5-pentanediamine	1,5-diamino-2-methylpentane / 1,5-pentanediamine, 2-methyl-	CAS-No.: 15520-10-2	25 – 35	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	10 – 25	Carc. 1A, H350
Phenol, styrenated	Phenol, styrenated	CAS-No.: 61788-44-1	5 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
m-Xylylenediamine	-	CAS-No.: 1477-55-0	5 – <8	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Aluminum oxide (Al ₂ O ₃)	-	CAS-No.: 1344-28-1	5 – 10	Not classified
2,4,6-tris(dimethylaminomethyl)phenol	2,4,6-tris(dimethylamino methyl)phenol 2,4,6-tris(dimethylamino methyl)phenol	CAS-No.: 90-72-2	1 – 2.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
3-Aminopropyltriethoxysilan	3-aminopropyltriethoxysilane	CAS-No.: 919-30-2	1 – 2.5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Comply with applicable regulations.

Storage conditions

Protect from sunlight. Store in a well-ventilated place.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Heat and ignition sources

Keep away from heat and direct sunlight.

Storage temperature

5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure good ventilation of the work station.

Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:

Long sleeved protective clothing

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4	

Eye protection:

Wear security glasses which protect from splashes

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red
Odour	Amine-like
Odour threshold	No data available
pH	11.5
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.31 g/cm ³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	50 – 70 Pa·s HN-0333
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	Corrosive vapours.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
LD50 dermal rat	1870 mg/kg
LC50 Inhalation - Rat	4.9 mg/l

Aluminum oxide (Al ₂ O ₃) (1344-28-1)	
LD50 oral rat	> 15900 mg/kg
LC50 Inhalation - Rat	7.6 mg/l

Phenol, styrenated (61788-44-1)	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	158.31 mg/l/4h

m-Xylylenediamine (1477-55-0)	
LD50 oral rat	1090 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1.34 mg/l/4h

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)

3-Aminopropyltriethoxysilan (919-30-2)	
LD50 oral rat	1.57 – 2.83 ml/kg (EPA OTS 798.1175, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	4.29 ml/kg (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	> 5 ppm (OECD 403: Acute Inhalation Toxicity, 6 h, Rat, Male, Experimental value, Inhalation (vapours))

Skin corrosion/irritation	Causes severe skin burns. pH: 11.5
Serious eye damage/irritation	Assumed to cause serious eye damage pH: 11.5
Respiratory or skin sensitization	May cause an allergic skin reaction.



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Quartz (SiO ₂) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.
2-methyl-1,5-pentanediamine (15520-10-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 - Fish [1]	130 mg/l (LC50; 48 h)
NOEC (acute)	1000 mg/l
LOEC (acute)	1800 mg/l
Phenol, styrenated (61788-44-1)	
LC50 - Fish [1]	5.6 mg/l
LC50 - Other aquatic organisms [1]	9.7 mg/l
EC50 - Crustacea [1]	1.44 mg/l
EC50 72h - Algae [1]	0.326 mg/l (Algae, Literature study)
NOEC (acute)	3.2 mg/l
Threshold limit - Algae [1]	0.326 mg/l (72 h; Algae)
Threshold limit - Algae [2]	0.14 mg/l (72 h; Algae)
m-Xylylenediamine (1477-55-0)	
LC50 - Fish [1]	75 mg/l
LC50 - Other aquatic organisms [1]	20.3 ppb
EC50 - Crustacea [1]	15 mg/l



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

m-Xylylenediamine (1477-55-0)	
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l
NOEC (acute)	10.5 mg/kg
LOEC (chronic)	15 mg/l
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 - Fish [1]	> 100 mg/l (96 h; Pisces; Nominal concentration)
LC50 - Fish [2]	70.9 mg/l (96 h; Pisces)
EC50 - Other aquatic organisms [1]	84 mg/l (72 h; Desmodesmus subspicatus; growth rate; ECHA)
ErC50 algae	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)
Threshold limit - Algae [1]	10 - 100, Algae
Threshold limit - Algae [2]	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
3-Aminopropyltriethoxysilan (919-30-2)	
LC50 - Fish [1]	> 934 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	331 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 1000 mg/l (EU Method C.3, 72 h, Scenedesmus subspicatus, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

HIT-RE 500 V3, B	
Persistence and degradability	May cause long-term adverse effects in the environment.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Phenol, styrenated (61788-44-1)	
Biochemical oxygen demand (BOD)	0.000231 g O ₂ /g substance
Chemical oxygen demand (COD)	0.004827 g O ₂ /g substance
3-Aminopropyltriethoxysilan (919-30-2)	
Persistence and degradability	Not readily biodegradable in water.

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.3. Bioaccumulative potential

HIT-RE 500 V3, B	
Bioaccumulative potential	Not established.
2-methyl-1,5-pentanediamine (15520-10-2)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
Phenol, styrenated (61788-44-1)	
Bioaccumulative potential	Bioaccumulative potential.
BCF - Fish [1]	3246 l/kg (BCFBAF v3.01, Pisces, Fresh water, Weight of evidence, Fresh weight)
BCF - Fish [2]	3246 mg/l
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
3-Aminopropyltriethoxysilan (919-30-2)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	3.4 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)

12.4. Mobility in soil

2-methyl-1,5-pentanediamine (15520-10-2)	
Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
Phenol, styrenated (61788-44-1)	
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
3-Aminopropyltriethoxysilan (919-30-2)	
Ecology - soil	No (test)data on mobility of the substance available.

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 3259	UN 3259	UN 3259	UN 3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
14.3. Transport hazard class(es)			
8	8	8	8
			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.6. Special precautions for user

Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	2
Orange plates	



Tunnel restriction code (ADR)	E
-------------------------------	---

Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
MFAG-No	154

Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-RE 500 V3, B	
Canada DSL NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Quartz (SiO ₂) (14808-60-7)
Listed on the Canadian DSL (Domestic Substances List)

Aluminum oxide (Al ₂ O ₃) (1344-28-1)
Listed on the Canadian DSL (Domestic Substances List)



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

m-Xylylenediamine (1477-55-0)

Listed on the Canadian DSL (Domestic Substances List)

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Listed on the Canadian DSL (Domestic Substances List)

3-Aminopropyltriethoxysilan (919-30-2)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

SDS Major/Minor None
Issue date 12-08-2022
Revision date 12-08-2022
Supersedes 05-13-2020

Other information None.

Full text of H-statements:

H227	Combustible liquid
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Abbreviations and acronyms:	
IATA	International Air Transport Association
EC50	Median effective concentration
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V3

Safety information for 2-Component-products

Issue date: 08/05/2023

Revision date: 08/05/2023

Supersedes: 13/05/2020

Version: 2.4

SECTION 1: Kit identification

1.1 Product identifier

Trade name

HIT-RE 500 V3



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification (GHS CA)

Skin corrosion/irritation, Category 1B	H314
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 2	H341
Reproductive toxicity, Category 1B	H360
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335

Label elements

GHS CA labelling

Hazard pictograms (GHS CA)



GHS05



GHS07



GHS08

Signal word (GHS CA)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS CA)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H335 - May cause respiratory irritation.
H341 - Suspected of causing genetic defects (oral).

HIT-RE 500 V3


Safety information for 2-Component-products

Precautionary statements (GHS CA)

H360 - May damage fertility. (oral).
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

Additional information

2-component-foilpack, contains:
Component A: Epoxy resin, Reactive diluent, inorganic filler
Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	Classification (GHS CA)
HIT-RE 500 V3, B		1	pcs (pieces)	Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335
HIT-RE 500 V3, A (GHS08)		1	pcs (pieces)	Skin Corr. 1C, H314 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters
Notify authorities if liquid enters sewers or public waters
Avoid release to the environment
Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.
After curing, the product can be disposed of with household waste.

Storage conditions

Protect from sunlight. Store in a well-ventilated place.

Technical measures

Comply with applicable regulations

Precautions for safe handling

Wear personal protective equipment
Avoid contact with skin and eyes
Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
Avoid contact during pregnancy/while nursing

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation
Mechanically recover the product
On land, sweep or shovel into suitable containers
Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition
Direct sunlight

HIT-RE 500 V3

Safety information for 2-Component-products

Incompatible products

Strong bases

Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact

Get immediate medical advice/attention.
Immediately rinse with water for a prolonged period while holding the eyelids wide open
Remove contact lenses, if present and easy to do. Continue rinsing.
Consult an eye specialist

First-aid measures after ingestion

Do not induce vomiting
Rinse mouth
Immediately call a POISON CENTER/doctor.

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact

Wash with plenty of water/...
Take off immediately all contaminated clothing.
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get immediate medical advice/attention.

First-aid measures general

Never give anything by mouth to an unconscious person
If you feel unwell, seek medical advice (show the label where possible)

Symptoms/effects

Causes severe skin burns and eye damage.

Symptoms/effects after eye contact

Causes serious eye damage.

Symptoms/effects after skin contact

May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions

Use water spray or fog for cooling exposed containers
Exercise caution when fighting any chemical fire
Prevent fire fighting water from entering the environment

Protection during firefighting

Self-contained breathing apparatus
Do not enter fire area without proper protective equipment, including respiratory protection

Hazardous decomposition products in case of fire

Thermal decomposition generates :
Carbon dioxide
Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 05/08/2023

Revision date: 05/08/2023

Supersedes: 05/13/2020

Version: 2.4

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Trade name	HIT-RE 500 V3, A
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.3. Supplier

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
Mississauga, Ontario, L5N 6S2
Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
Kaufering, 86916
Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec
	Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada)
	Tel.: 703 527 3887 (Other countries)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin corrosion/irritation, Category 1C	H314	Causes severe skin burns and eye damage.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Germ cell mutagenicity, Category 2	H341	Suspected of causing genetic defects.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Danger

Hazard statements (GHS CA)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H341 - Suspected of causing genetic defects.
H360 - May damage fertility or the unborn child.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	25 – 40	Carc. 1A, H350
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane / 2,2-bis(4-(2,3-epoxypropyloxy)phenyl)propane / 2,2-bis(4-glycidyloxyphenyl)propane	CAS-No.: 1675-54-3	25 – 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	-	CAS-No.: 9003-36-5	10 – 25	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
butanedioldiglycidyl ether	1,4-bis(2,3-epoxypropoxy)butane; butanedioldiglycidyl ether / 1,4-bis(2,3-epoxypropoxy)butane / 1,4-bis(2,3-epoxypropyloxy)butane / 1,4-bis(glycidyloxy)butane	CAS-No.: 2425-79-8	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
1,3 Propanediol, 2 ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane	-	CAS-No.: 30499-70-8	5 – 10	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 1B, H360



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	((3-(trimethoxysilyl)propoxy)methyl)oxirane / [3-(2,3-epoxypropoxy)propyl]trimethoxysilane / 1-(glycidyloxy)-3-(trimethoxysilyl)propane	CAS-No.: 2530-83-8	2.5 – 5	Eye Dam. 1, H318 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
---------------------------	---



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Protection during firefighting

Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Spilled material may present a slipping hazard.

6.2. Methods and materials for containment and cleaning up

For containment

Collect spillage.

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.

Other information

Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Protect from sunlight.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Heat and ignition sources

Keep away from heat and direct sunlight.

Storage temperature

5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls

No specific measures identified.

Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Materials for protective clothing:

Long sleeved protective clothing

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4	

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	No data available
pH	6.6
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.45 g/cm³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Viscosity, kinematic	No data available
Viscosity, dynamic	45 – 59 Pa·s 23 °C
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 oral	11400 mg/kg
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)

butanedioldiglycidyl ether (2425-79-8)	
LD50 oral rat	2980 mg/kg (Rat)
LD50 oral	1163 mg/kg (Rat; Exp. Key study ECHA)
LD50 dermal rat	> 2150 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rat, Male / female, Experimental value, Dermal, 7 day(s))
LD50 dermal rabbit	1130 mg/kg (Rabbit)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)

Skin corrosion/irritation	Causes severe skin burns. pH: 6.6
Serious eye damage/irritation	Assumed to cause serious eye damage pH: 6.6

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Not classified
Quartz (SiO₂) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LC50 - Fish [1]	1.2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
LC50 - Fish [2]	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
Threshold limit - Algae [1]	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit - Algae [2]	4.2 mg/l (72 h; Scenedesmus sp.)
butanedioldiglycidyl ether (2425-79-8)	
LC50 - Fish [1]	24 mg/l (96 h; Pisces) ECHA
LC50 - Other aquatic organisms [1]	> 160 mg/l
NOEC (acute)	40 mg/l
Threshold limit - Algae [1]	88930 mg/l (96 h; Algae)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LC50 - Fish [1]	55 mg/l (96 h; Cyprinus carpio; Young)
LC50 - Fish [2]	237 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
EC50 - Crustacea [1]	473 – 710 mg/l (48 h; Daphnia magna)
Threshold limit - Algae [1]	119 mg/l (7 days; Anabaena flosaquae)
Threshold limit - Algae [2]	250 mg/l (72 h; Selenastrum capricornutum)

12.2. Persistence and degradability

HIT-RE 500 V3, A	
Persistence and degradability	May cause long-term adverse effects in the environment.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
butanedioldiglycidyl ether (2425-79-8)	
Biochemical oxygen demand (BOD)	0.01982 g O ₂ /g substance

12.3. Bioaccumulative potential

HIT-RE 500 V3, A	
Bioaccumulative potential	Not established.
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
butanedioldiglycidyl ether (2425-79-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.27 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)

12.4. Mobility in soil

Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Ecology - soil	No (test)data on mobility of the substance available.

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

butanedioldiglycidyl ether (2425-79-8)	
Surface tension	44.4 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.1 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 1759	UN 1759	UN 1759	UN 1759
14.2. UN proper shipping name			
CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	Corrosive solid, n.o.s. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)
Transport document description			
UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1759 Corrosive solid, n.o.s. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
8	8	8	8
14.4. Packing group			
III	III	III	III



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ADR	IMDG	IATA	RID
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	C10
Special provisions (ADR)	274
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR)

E

Transport by sea

Special provisions (IMDG)	223, 274
Packing instructions (IMDG)	P002, LP02
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A

Air transport

PCA packing instructions (IATA)	860
PCA max net quantity (IATA)	25kg
CAO packing instructions (IATA)	864
Special provisions (IATA)	A3, A803

Rail transport

Special provisions (RID)	274
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-RE 500 V3, A

Canada DSL NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)
-----------------------	---

SECTION 16: Other information



according to the Hazardous Products Regulation (February 11, 2015)

Other information	None.
-------------------	-------

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
EC50	Median effective concentration
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration



HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Abbreviations and acronyms:	
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 05/08/2023

Revision date: 05/08/2023

Supersedes: 05/13/2020

Version: 1.5

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500 V3, B
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.3. Supplier

Supplier

Hilti (Canada) Corp.
2360 Meadowpine Boulevard
Mississauga, Ontario, L5N 6S2
Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
Kaufering, 86916
Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec
	Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada)
	Tel.: 703 527 3887 (Other countries)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin corrosion/irritation, Category 1B	H314	Causes severe skin burns and eye damage.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3,	H335	May cause respiratory irritation.
Respiratory tract irritation		
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Danger

Hazard statements (GHS CA)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H335 - May cause respiratory irritation.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
2-methyl-1,5-pentanediamine	1,5-diamino-2-methylpentane / 1,5-pentanediamine, 2-methyl-	CAS-No.: 15520-10-2	25 – 35	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	10 – 25	Carc. 1A, H350
Phenol, styrenated	Phenol, styrenated / Wingstay S	CAS-No.: 61788-44-1	5 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
m-Xylylenediamine	-	CAS-No.: 1477-55-0	5 – <8	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	2,4,6-tris(dimethylamino methyl)phenol 2,4,6-tris(dimethylamino methyl)phenol / tris-2,4,6-(dimethylaminomethyl)phenol	CAS-No.: 90-72-2	1 – 2.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
3-Aminopropyltriethoxysilan	3-aminopropyltriethoxysilane	CAS-No.: 919-30-2	1 – 2.5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Skin Sens. 1, H317

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	Do not use a heavy water stream.
--------------------------------	----------------------------------

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
-----------------	-------------------



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Comply with applicable regulations.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Heat and ignition sources	Keep away from heat and direct sunlight.
Storage temperature	5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.
------------------------	--

8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure good ventilation of the work station.
Environmental exposure controls	No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:

Long sleeved protective clothing

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4	

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red
Odour	Amine-like
Odour threshold	No data available
pH	11.5
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.31 g/cm ³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	50 – 70 Pa·s HN-0333
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	Corrosive vapours.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
LD50 dermal rat	1870 mg/kg
LC50 Inhalation - Rat	4.9 mg/l

Phenol, styrenated (61788-44-1)	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	158.31 mg/l/4h

m-Xylylenediamine (1477-55-0)	
LD50 oral rat	1090 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1.34 mg/l/4h

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)

3-Aminopropyltriethoxysilan (919-30-2)	
LD50 oral rat	1.57 – 2.83 ml/kg (EPA OTS 798.1175, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	4.29 ml/kg (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	> 5 ppm (OECD 403: Acute Inhalation Toxicity, 6 h, Rat, Male, Experimental value, Inhalation (vapours))

Skin corrosion/irritation	Causes severe skin burns. pH: 11.5
Serious eye damage/irritation	Assumed to cause serious eye damage pH: 11.5
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Quartz (SiO ₂) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.
2-methyl-1,5-pentanediamine (15520-10-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 - Fish [1]	130 mg/l (LC50; 48 h)
NOEC (acute)	1000 mg/l
LOEC (acute)	1800 mg/l
Phenol, styrenated (61788-44-1)	
LC50 - Fish [1]	5.6 mg/l
LC50 - Other aquatic organisms [1]	9.7 mg/l
EC50 - Crustacea [1]	1.44 mg/l
EC50 72h - Algae [1]	0.326 mg/l (Algae, Literature study)
NOEC (acute)	3.2 mg/l
Threshold limit - Algae [1]	0.326 mg/l (72 h; Algae)
Threshold limit - Algae [2]	0.14 mg/l (72 h; Algae)
m-Xylylenediamine (1477-55-0)	
LC50 - Fish [1]	75 mg/l
LC50 - Other aquatic organisms [1]	20.3 ppb
EC50 - Crustacea [1]	15 mg/l
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

m-Xylylenediamine (1477-55-0)	
NOEC (acute)	10.5 mg/kg
LOEC (chronic)	15 mg/l
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 - Fish [1]	> 100 mg/l (96 h; Pisces; Nominal concentration)
LC50 - Fish [2]	70.9 mg/l (96 h; Pisces)
EC50 - Other aquatic organisms [1]	84 mg/l (72 h; Desmodesmus subspicatus; growth rate; ECHA)
ErC50 algae	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)
Threshold limit - Algae [1]	10 - 100, Algae
Threshold limit - Algae [2]	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
3-Aminopropyltriethoxysilan (919-30-2)	
LC50 - Fish [1]	> 934 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	331 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 1000 mg/l (EU Method C.3, 72 h, Scenedesmus subspicatus, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

HIT-RE 500 V3, B	
Persistence and degradability	May cause long-term adverse effects in the environment.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Phenol, styrenated (61788-44-1)	
Biochemical oxygen demand (BOD)	0.000231 g O ₂ /g substance
Chemical oxygen demand (COD)	0.004827 g O ₂ /g substance
3-Aminopropyltriethoxysilan (919-30-2)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-RE 500 V3, B	
Bioaccumulative potential	Not established.



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-methyl-1,5-pentanediamine (15520-10-2)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
Phenol, styrenated (61788-44-1)	
Bioaccumulative potential	Bioaccumulative potential.
BCF - Fish [1]	3246 l/kg (BCFBAF v3.01, Pisces, Fresh water, Weight of evidence, Fresh weight)
BCF - Fish [2]	3246 mg/l
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
3-Aminopropyltriethoxysilan (919-30-2)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	3.4 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)

12.4. Mobility in soil

2-methyl-1,5-pentanediamine (15520-10-2)	
Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
Phenol, styrenated (61788-44-1)	
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Surface tension	No data available in the literature
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
3-Aminopropyltriethoxysilan (919-30-2)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Ozone	Not classified
-------	----------------

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Other information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)

Disposal must be done according to official regulations.

Product/Packaging disposal recommendations

After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.
Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials

Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 3259	UN 3259	UN 3259	UN 3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
14.3. Transport hazard class(es)			
8	8	8	8
			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)

C8

Special provisions (ADR)

274



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	2
Orange plates	



Tunnel restriction code (ADR)	E
-------------------------------	---

Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
MFAG-No	154

Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-RE 500 V3, B

Canada DSL NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)
-----------------------	---

SECTION 16: Other information

SDS Major/Minor	None
Issue date	05-08-2023
Revision date	05-08-2023
Supersedes	05-13-2020

Other information	None.
-------------------	-------

Full text of H-statements:

H227	Combustible liquid
------	--------------------



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of H-statements:	
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
IATA	International Air Transport Association
EC50	Median effective concentration
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative



HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.